NEW PRODUCT GUIDE



STREET FLEX for LEXUS CT200h (ZWA10) Available Mid July!



Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
LEXUS	GSQ36-51AS3							[Upon EDFC Installation]
CT200H	JPY 148,000	Ft : 4.0	Ft : -35	Ft: -45 to -25	Ft: -73 to -3	Mid		Ft: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle.
ZWA10	JF1 146,000	Rr : 5.0	Rr : -30	Rr: -40 to -15	Rr: -60 to -15	July		Rr: Cover above mount needs to be removed. Interior needs to be cut or
1800 cc / FWD	JAN: 4582202758409							removed, to avoid interference.

*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.







*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection. TEIN dampers are designed to comply with the regulations at the standard ride height drop.

COMPATIBILITY INFORMATION



Compatibility Confirmed on TOYOTA MARK X ZIO (ANA15)!

STREET BASIS

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	Remarks
TOYOTA MARK X ZIO ANA15 2400 cc / AWD	GSQ10-11AS2 JPY 90,000 JAN: 4582202755835	Ft : 4.0 Rr : 6.5	Ft : -50 Rr : -40	Ft:-60 to -40 Rr:-50 to -33	Ft: -80 to -24 Rr: -76 to -33	Available Now!	Spring seat position: Ft = 30mm / Rr = HAS 50mm

STREET ADUANCE

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
TOYOTA MARK X ZIO ANA15 2400 cc / AWD	GSQ10-21AS2 JPY 105,000 JAN: 4582202756221	Ft : 4.0 Rr : 6.5	Ft : -50 Rr : -40	Ft: -60 to -40 Rr: -50 to -33	Ft: -80 to -24 Rr: -76 to -33	Available Now!	NOT Compatible	Spring seat position: Ft = 30mm / Rr = HAS 50mm







*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection. TEIN dampers are designed to comply with the regulations at the standard ride height drop.

For product information, please contact:

TEIN INC. Sales Section
Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123
http://www.tein.co.jp/global_en.html
E-mail os-inquiry@tein.co.jp

