

## MONO SPORT Damper Kit for Honda Integra & Integra Type R (DC5) Available Soon!

# MONO Sport DAMPER

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Setting	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Series Fitting	Remarks
HONDA INTEGRA DC5 ( IS ) 2000 cc / FWD	GSA02-71SS1 JPY 198,000 JAN : 4582202759017	SPORT	Ft: 12.0 Rr: 14.0	Ft: -30 Rr: -30	Ft: -40 to -20 Rr: -40 to -20	Ft: -53 to -2 Rr: -66 to +2	Mid February	MOTOR KIT: EDK05-12140 STRUT KIT: EDK06-K4474	Because the adjustable range of the camber angle is limited due to the vehicle characteristics, adjust the angle within the appropriate adjustable range of the toe angle. [Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed. Rr: Motor needs to be installed as parallel to vehicle body as possible, due to insufficient clearance.
HONDA INTEGRA DC5 ( TYPE S ) 2000 cc / FWD	GSA02-71SS1 JPY 198,000 JAN : 4582202759017	SPORT	Ft: 12.0 Rr: 14.0	Ft: -30 Rr: -30	Ft: -40 to -20 Rr: -40 to -20	Ft: -53 to -2 Rr: -66 to +2	Mid February	MOTOR KIT: EDK05-12140 STRUT KIT: EDK06-K4474	Because the adjustable range of the camber angle is limited due to the vehicle characteristics, adjust the angle within the appropriate adjustable range of the toe angle. [Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed. OE strut bar needs to be removed. Rr: Motor needs to be installed as parallel to vehicle body as possible, due to insufficient clearance.
HONDA INTEGRA TYPE R DC5 (2001.07-2004.09) 2000 cc / FWD	GSA02-71SS1 JPY 198,000 JAN : 4582202759017	SPORT	Ft: 12.0 Rr: 14.0	Ft: -30 Rr: -30	Ft: -40 to -20 Rr: -40 to -20	Ft: -53 to -2 Rr: -66 to +2	Mid February	MOTOR KIT: EDK05-12140 STRUT KIT: EDK06-K4474	Because the adjustable range of the camber angle is limited due to the vehicle characteristics, adjust the angle within the appropriate adjustable range of the toe angle. [Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed. Rr: Motor needs to be installed as parallel to vehicle body as possible, due to insufficient clearance.
HONDA INTEGRA TYPE R DC5 (2004.09-2006.07) 2000 cc / FWD	GSA02-71SS1 JPY 198,000 JAN : 4582202759017	SPORT	Ft: 12.0 Rr: 14.0	Ft: -30 Rr: -30	Ft: -40 to -20 Rr: -40 to -20	Ft: -53 to -2 Rr: -66 to +2	Mid February	MOTOR KIT: EDK05-12140 STRUT KIT: EDK06-K4474	Because the adjustable range of the camber angle is limited due to the vehicle characteristics, adjust the angle within the appropriate adjustable range of the toe angle. [Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed. OE strut bar needs to be removed. Rr: Motor needs to be installed as parallel to vehicle body as possible, due to insufficient clearance.

\*For EDFC Series, Controller kit (sold separately) is required, in addition to Motor Kit etc noted in the chart



\*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp).

Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations.

For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection.

TEIN dampers are designed to comply with the regulations at the standard ride height drop.

For product information, please contact:

TEIN INC. Sales Section

Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123

Web [http://www.tein.co.jp/global\\_en.html](http://www.tein.co.jp/global_en.html)

E-mail [os-inquiry@tein.co.jp](mailto:os-inquiry@tein.co.jp)

