

NEW PRODUCT GUIDE



For Sale Late March !

STREET FLEX for HONDA ACCORD (CU2) and ACCORD TOURER (CW1/CW2) !!

STREET FLEX

DAMPER

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
HONDA ACCORD CU2 2400 cc / FWD	GSB90-51SS3 JPY 128,000 JAN : 4582202757990	Ft : 10.0 Rr : 5.0	Ft : -35 Rr : -25	Ft: -45 to -25 Rr: -35 to -15	Ft: -92 to -8 Rr: -68 to +23	Late March	EDK05-12120	[Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle.
HONDA ACCORD TOURER CW1 2000 cc / FWD			Ft : -35 Rr : -30	Ft: -45 to -25 Rr: -40 to -20	Ft: -92 to -8 Rr: -73 to +18			[Upon EDFC Installation] Rr: Interior needs to be cut, to avoid interference.
HONDA ACCORD TOURER CW2 2400 cc / FWD			Ft : -25 Rr : -25	Ft: -35 to -15 Rr: -35 to -15	Ft: -79 to +5 Rr: -73 to +18			[Upon EDFC Installation] Rr: Interior needs to be cut, to avoid interference.

*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.



*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection. TEIN dampers are designed to comply with the regulations at the standard ride height drop.

For product information, please contact:
 TEIN INC. Sales Section
 Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123
http://www.tein.co.jp/global_en.html
 E-mail os-inquiry@tein.co.jp

