

# NEW PRODUCT GUIDE

**NOW AVAILABLE ! STREET FLEX for HONDA FIT (GE6/GE8) & FIT HYBRID (GP1/GP4) !!**

## STREET FLEX

DAMPER

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
HONDA FIT GE6 1300 cc / FWD	GSB80-41AS2 JPY 138,000 JAN : 4582202757839	Ft: 4.0 Rr: 2.0	Ft: -50 Rr: -50	Ft: -60 to -40 Rr: -60 to -40	Ft: -93 to -31 Rr: -69 to -36	Available NOW!	NOT Compatible	Rr: Interior service hole cover needs to be removed or modified.
HONDA FIT GE8 1500 cc / FWD			Ft: -35 Rr: -35	Ft: -45 to -25 Rr: -45 to -25	Ft: -78 to -16 Rr: -54 to -21		NOT Compatible	
HONDA FIT HYBRID GP1 1300 cc / FWD			Ft: -40 Rr: -35	Ft: -50 to -30 Rr: -45 to -30	Ft: -78 to -16 Rr: -63 to -30		NOT Compatible	
HONDA FIT HYBRID GP4 1500 cc / FWD			Ft: -40 Rr: -45	Ft: -50 to -30 Rr: -55 to -45	Ft: -88 to -26 Rr: -78 to -45		NOT Compatible	



\*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection. TEIN dampers are designed to comply with the regulations at the standard ride height drop.

**For product information, please contact:**  
TEIN INC. Sales Section  
Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123  
[http://www.tein.co.jp/global\\_en.html](http://www.tein.co.jp/global_en.html)  
E-mail [os-inquiry@tein.co.jp](mailto:os-inquiry@tein.co.jp)

