NEW PRODUCT GUIDE





More & More Additions to "STREET FLEX" Lineups!

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
HONDA ODYSSEY RA7 (ABSOLUTE) 2300 cc / AWD	GSA74-51AS3 JPY 138,000 JAN: 4582202758218	Ft : 10.0 Rr : 8.0	Ft : -45 Rr : -50	Ft:-55 to -35 Rr:-60 to -40	Ft:-131 to -4 Rr:-90 to -36	Early August	EDK05-12120	[Upon EDFC Installation] Rr: NOT compatible with vehicle which has automatic air conditioner line on right side.
HONDA ODYSSEY RA7 (S, M, L) 2300 cc / AWD	GSA74-51AS3 JPY 138,000 JAN: 4582202758218	Ft : 10.0 Rr : 8.0	Ft : -60 Rr : -70	Ft:-70 to -50 Rr:-80 to -60	Ft:-141 to -15 Rr:-110 to -56	Early August	EDK05-12120	[Upon EDFC Installation] Rr: NOT compatible with vehicle which has automatic air conditioner line on right side.
HONDA ODYSSEY RA9 (ABSOLUTE) 3000 cc / AWD	GSA74-51AS3 JPY 138,000 JAN: 4582202758218	Ft : 10.0 Rr : 8.0	Ft : -45 Rr : -50	Ft:-55 to -35 Rr:-60 to -45	Ft:-131 to -19 Rr:-99 to -45	Early August	EDK05-12120	[Upon EDFC Installation] Rr: NOT compatible with vehicle which has automatic air conditioner line on right side.
HONDA ODYSSEY RA9 (VG, VZ) 3000 cc / AWD	GSA74-51AS3 JPY 138,000 JAN: 4582202758218	Ft : 10.0 Rr : 8.0	Ft : -60 Rr : -70	Ft:-70 to -50 Rr:-80 to -65	Ft:-146 to -34 Rr:-119 to -65	Early August	EDK05-12120	[Upon EDFC Installation] Rr: NOT compatible with vehicle which has automatic air conditioner line on right side.
HONDA STEP WGN RG1 2000 cc / FWD	GSB18-51AS3 JPY 148,000 JAN: 4582202758393	Ft : 5.0 Rr : 4.0	Ft : -35 Rr : -40	Ft:-45 to -25 Rr:-50 to -37	Ft:-100 to -16 Rr:-69 to -37	Early August	EDK05-12120	Rr: NOT Full-Length Adjustable. [Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Motor and its joint part need to be waterproofed with silicon sealant.
HONDA STEP WGN RG3 2400 cc / FWD	GSB18-51AS3 JPY 148,000 JAN: 4582202758393	Ft : 5.0 Rr : 4.0	Ft : -30 Rr : -40	Ft:-40 to -20 Rr:-50 to -37	Ft: -95 to -11 Rr: -69 to -37	Early August	EDK05-12120	Rr: NOT Full-Length Adjustable. [Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Motor and its joint part need to be waterproofed with silicon sealant.
HONDA STEP WGN SPADA RK6 2000 cc / AWD	GSHA4-51AS3 JPY 148,000 JAN: 4582202758324	Ft : 6.0 Rr : 6.0	Ft : -40 Rr : -50	Ft:-50 to -30 Rr:-60 to -40	Ft: -82 to -7 Rr: -73 to -40	Early August	EDK05-12120	[Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Motor and its joint part need to be waterproofed with silicon sealant.
HONDA PRELUDE BB6 2200 cc / FWD	GSH92-51SS3 JPY 128,000 JAN: 4582202758423	Ft : 10.0 Rr : 6.0	Ft : -30 Rr : -55	Ft:-40 to -20 Rr:-65 to -45	Ft:-119 to +1 Rr:-162 to +8	Early August	EDK05-12120	[Upon EDFC Installation] Rr: Interior needs to be cut, if it interferes with motor.
HONDA PRELUDE BB8 2200 cc / FWD	GSH92-51SS3 JPY 128,000 JAN: 4582202758423	Ft : 10.0 Rr : 6.0	Ft : -30 Rr : -55	Ft:-40 to -20 Rr:-65 to -45	Ft:-119 to +1 Rr:-162 to +8	Early August	EDK05-12120	[Upon EDFC Installation] Rr: Interior needs to be cut, if it interferes with motor.

^{*}For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart

For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection.

TEIN dampers are designed to comply with the regulations at the standard ride height drop.

For product information, please contact:

TEIN INC. Sales Section
Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123
http://www.tein.co.jp/global_en.html
E-mail os-inquiry@tein.co.jp



^{*}For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations.