

COMPATIBILITY INFORMATION



***STREET FLEX is now confirmed compatible on
LEXUS GS350 (GRS191), GS430 (UZS190) and GS450h (GWS191) !***

STREET FLEX
DAMPER

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
LEXUS GS350 GRS191 3500 cc / RWD	GSC76-51SS3 JPY 128,000 JAN : 4582202757433	Ft : 10.0 Rr : 8.0	Ft : -35 Rr : -35	Ft : -45 to -25 Rr : -45 to -25	Ft : -105 to +10 Rr : -144 to +20	Available Now!	EDK05-12120	Ft: Set case length -2mm, and the position of spring seat -3mm compared to GRS200.
LEXUS GS430 UZS190 4300 cc / RWD			Ft : -40 Rr : -25	Ft : -50 to -30 Rr : -35 to -15	Ft : -105 to +10 Rr : -144 to +20			Ft: Set case length -2mm, and the position of spring seat -3mm compared to GRS200.
LEXUS GS450h GWS191 3500 cc / RWD			Ft : -35 Rr : -25	Ft : -45 to -25 Rr : -35 to -15	Ft : -105 to +10 Rr : -144 to +20			Ft: Set case length -2mm compared to GRS200. Rr: Set case length +7mm, and the position of spring seat +6mm compared to GRS200.

*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.



*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection. TEIN dampers are designed to comply with the regulations at the standard ride height drop.

For product information, please contact:
 TEIN INC. Sales Section
 Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123
http://www.tein.co.jp/global_en.html
 E-mail os-inquiry@tein.co.jp

