

More "STREET FLEX" Lineups Available Mid September! Skyline (PV36/KV36), Fuga (PY50) & Fairlady Z (Z34)!



Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
NISSAN SKYLINE PV36 3500 cc / RWD	GSP92-51AS3 JPY 138,000 JAN : 4582202758270	Ft : 12.0 Rr : 10.0	Ft : -35 Rr : -40	Ft : -45 to -25 Rr : -50 to -30		Mid September	EDK05-12120	[Upon EDFC Installation] Ft: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Rr: Motor needs to be waterproofed with silicon sealant.
NISSAN SKYLINE KV36 3700 cc / RWD	GSP92-51AS3 JPY 138,000 JAN : 4582202758270	Ft : 12.0 Rr : 10.0	Ft : -35 Rr : -35	Ft : -45 to -25 Rr : -45 to -25		Mid September		[Upon EDFC Installation] Ft: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Rr: Motor needs to be waterproofed with silicon sealant.
NISSAN FUGA PY50 3500 cc / RWD	GSP54-51AS3 JPY 138,000 JAN : 4582202758577	Ft : 10.0 Rr : 10.0	Ft : -40 Rr : -30	Ft : -50 to -30 Rr : -40 to -20		Mid September	EDK05-12120	[Upon EDFC Installation] Ft/Rr: Motor needs to be installed onto shock absorber and checked fo proper operation, before installing to the vehicle. Rr: Strut tower needs to be pierced.
NISSAN FAIRLADY Z Z34 3700 cc / RWD	GSP92-51AS3 JPY 138,000 JAN : 4582202758270	Ft : 12.0 Rr : 10.0	Ft : -25 Rr : -25	Ft : -35 to -15 Rr : -35 to -15		Mid September	EDK05-12120	[Upon EDFC Installation] Ft: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Rr: Motor needs to be waterproofed with silicon sealant.







*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection.

TEIN dampers are designed to comply with the regulations at the standard ride height drop.





"STREET BASIS" for Wish (ZNE10G) has NEW Part Number Now!

STREET BASIS

*Old Kit (Part No. GSL34-11SS2) has been discontinued and is no longer available.

Vehicle Make / I Chassis Coo Displacement / Dri	de	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	Remarks
ΤΟΥΟΤΑ		GSQ72-11SS2						
WISH		JPY 88,000	Ft: 4.0	Ft : -50	Ft: -60 to -40	Ft: -75 to -20	Available	
ZNE10G			Rr : 5.0	Rr : -40	Rr: -50 to -30	Rr: -66 to -1	Now!	
1800 cc / I	FWD JA	AN: 4582202758638						





*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection.

TEIN dampers are designed to comply with the regulations at the standard ride height drop.

For product information, please contact: TEIN INC. Sales Section Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123 http://www.tein.co.jp/global_en.html E-mail os-inquiry@tein.co.jp

