

## NEW PRODUCT GUIDE



### More & More Additions to Brand-New STREET FLEX Lineups!!

# STREET FLEX

DAMPER

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
NISSAN STAGEA NM35 2500 cc / AWD	GSP00-51AS3 JPY 138,000	Ft : 10.0 Rr : 9.0	Ft : -30 Rr : -15	Ft : -40 to -20 Rr : -25 to -5	Ft : -101 to +13 Rr : -40 to -2	Late February	EDK05-12120	NOT tested on AR-X Four model.
NISSAN STAGEA PNM35 3500 cc / AWD	JAN : 4582202757907		Ft : -15 Rr : -5	Ft : -25 to -5 Rr : -15 to +5	Ft : -93 to +21 Rr : -35 to +5			[Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber, before installing to the vehicle. Motor needs to be waterproofed.
SUBARU IMPREZA GC8 2000 cc / AWD	GSS12-51SS4 JPY 158,000	Ft : 6.0 Rr : 4.0	Ft : -30 Rr : -30	Ft : -40 to -20 Rr : -40 to -20	Ft : -101 to +7 Rr : -95 to +9	Late February	EDK05-12140 [STRUT KIT] EDK06-K4474	Avoid setting Rr spring seat below 165mm, to prevent interference with tire. [Upon EDFC Installation] Ft: Bonnet insulator needs to be cut or removed, to avoid interference. Rr: Motor needs to be installed at an angle where over 10mm clearance from seatbelt tensioner and harness can be secured. Harness might need to be relocated.
SUBARU IMPREZA SPORTS WAGON GF8 2000 cc / AWD	JAN : 4582202757921		Ft : -30 Rr : -25	Ft : -40 to -20 Rr : -35 to -15	Ft : -101 to +7 Rr : -96 to +7		NOT Tested Avoid setting Rr spring seat below 165mm, to prevent interference with tire.	
SUBARU IMPREZA GRB 2000 cc / AWD	GSS78-51SS1 JPY 148,000 JAN : 4582202757853	Ft : 7.0 Rr : 5.0	Ft : -30 Rr : -25	Ft : -40 to -20 Rr : -35 to -15	Ft : -83 to -15 Rr : -96 to +20	Late February	EDK05-12140 [STRUT KIT] EDK06-K4474	Rr: Interior needs to be cut, to avoid interference.
SUBARU IMPREZA GVB 2000 cc / AWD			Ft : -25 Rr : -25	Ft : -35 to -15 Rr : -35 to -15	Ft : -78 to -10 Rr : -96 to +20			
SUBARU IMPREZA GRF 2500 cc / AWD			Ft : -25 Rr : -25	Ft : -35 to -15 Rr : -35 to -15	Ft : -78 to -10 Rr : -96 to +20			
SUBARU IMPREZA GVF 2500 cc / AWD			Ft : -25 Rr : -20	Ft : -35 to -15 Rr : -30 to -10	Ft : -78 to -10 Rr : -91 to +25			

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
SUBARU LEGACY B4 BM9 (w/ Bilstein Suspension) 2500 cc / AWD	GSS92-51SS3 JPY 148,000 JAN : 4582202757877	Ft : 7.0 Rr : 6.0	Ft : -50 Rr : -35	Ft : -60 to -40 Rr : -45 to -25	Ft : -78 to -21 Rr : -111 to -12	Late February	EDK05-12120	Rr: Interior needs to be cut, to avoid interference.
SUBARU LEGACY TOURING WAGON BRG 2000 cc / AWD			Ft : -45 Rr : -50	Ft : -55 to -35 Rr : -60 to -40	Ft : -81 to -21 Rr : -131 to -32			
SUBARU LEGACY TOURING WAGON BR9 (w/o Bilstein Suspension) 2500 cc / AWD			Ft : -45 Rr : -50	Ft : -55 to -35 Rr : -60 to -40	Ft : -73 to -16 Rr : -129 to -27			
SUBARU LEGACY TOURING WAGON BR9 (w/ Bilstein Suspension) 2500 cc / AWD			Ft : -50 Rr : -50	Ft : -60 to -40 Rr : -60 to -40	Ft : -78 to -21 Rr : -128 to -27			
MAZDA AZ-WAGON MJ22S 660 cc / FWD	GSU68-51AS3 JPY 148,000 JAN : 4582202757945	Ft : 5.0 Rr : 2.2	Ft : -40 Rr : -45	Ft : -50 to -30 Rr : -55 to -45	Ft : -93 to -16 Rr : -58 to -45	Late February	NOT Compatible	Rr: NOT full-length adjustable.
SUZUKI WAGON R MH21S 660 cc / FWD			Ft : -40 Rr : -40	Ft : -50 to -30 Rr : -50 to -40	Ft : -91 to -16 Rr : -51 to -40			Rr: NOT full-length adjustable. Exclusively for 3rd and 4th (Dec 04+, VIN MH21S-830001 or later for RR-DI, MH21S-560001 or later for other Turbo, and MH21S-300001/MH21S-460001 or later for Non-Turbo/NA).
SUZUKI WAGON R MH21S 660 cc / AWD			Ft : -45 Rr : -50	Ft : -55 to -35 Rr : -60 to -50	Ft : -98 to -21 Rr : -63 to -50			
SUZUKI WAGON R / WAGON R STINGRAY MH22S 660 cc / FWD			Ft : -40 Rr : -45	Ft : -50 to -30 Rr : -55 to -45	Ft : -93 to -16 Rr : -58 to -45			
SUZUKI WAGON R / WAGON R STINGRAY MH22S 660 cc / AWD			Ft : -45 Rr : -50	Ft : -55 to -35 Rr : -60 to -50	Ft : -98 to -21 Rr : -63 to -50			Rr: NOT full-length adjustable.

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

\*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp).

Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations.

For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection.

TEIN dampers are designed to comply with the regulations at the standard ride height drop.

**For product information, please contact:**  
 TEIN INC. Sales Section  
 Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123  
[http://www.tein.co.jp/global\\_en.html](http://www.tein.co.jp/global_en.html)  
 E-mail [os-inquiry@tein.co.jp](mailto:os-inquiry@tein.co.jp)

