

## NEW PRODUCT GUIDE

### More Additions to the Popular STREET FLEX Lineup!

## STREET FLEX DAMPER

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop (mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
NISSAN FAIRLADY Z Z33 3500 cc / RWD	GSP24-51AS3 JPY 138,000 JAN : 4582202758003	Ft: 10.0 Rr: 9.0	Ft: -10 Rr: -10	Ft: -20 to 0 Rr: -20 to 0	Ft: -77 to +26 Rr: -60 to 0	Late March	EDK05-12120	Rr: Shock absorber needs to be detached from vehicle, when adjusting damping force. [Upon EDFC Installation] Ft/Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Rr: Strut tower needs to be pierced.
NISSAN FAIRLADY Z ROADSTER HZ33 3500 cc / RWD			Ft: -10 Rr: -5	Ft: -20 to 0 Rr: -15 to -3	Ft: -70 to +26 Rr: -63 to -3		NOT Compatible	Rr: Shock absorber needs to be detached from vehicle, when adjusting damping force.
NISSAN SKYLINE PV35 3500 cc / RWD			Ft: -35 Rr: -30	Ft: -45 to -25 Rr: -40 to -20	Ft: -103 to +1 Rr: -80 to -20		EDK05-12120	[Upon EDFC Installation] Ft: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Rr: Rubber cover above strut bar needs to be removed. Sponge behind rear seat might need to be cut if it interferes with the motor.
NISSAN SKYLINE COUPE CPV35 3500 cc / RWD			Ft: -20 Rr: -15	Ft: -30 to -10 Rr: -25 to -5	Ft: -87 to +16 Rr: -55 to +5		EDK05-12120	Rr: Shock absorber needs to be detached from vehicle, when adjusting damping force. [Upon EDFC Installation] Ft/Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Rr: Vehicle body needs to be pierced.
MITSUBISHI GALANT FORTIS CY4A 2000 cc / FWD	GSE20-51SS4 JPY 148,000 JAN : 4582202758010	Ft: 9.0 Rr: 7.0	Ft: -40 Rr: -35	Ft: -50 to -30 Rr: -45 to -25	Ft: -94 to -38 Rr: -76 to +1	Late March	EDK05-12140 [STRUT KIT] EDK06-K4474	[Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle.
MITSUBISHI GALANT FORTIS CY4A 2000 cc / AWD			Ft: -50 Rr: -50	Ft: -60 to -40 Rr: -60 to -40	Ft: -94 to -38 Rr: -91 to -16		EDK05-12140 [STRUT KIT] EDK06-K4474	[Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle.
MITSUBISHI GALANT FORTIS CY3A 1800 cc / FWD			Ft: -45 Rr: -40	Ft: -55 to -35 Rr: -50 to -30	Ft: -94 to -38 Rr: -81 to -4		EDK05-12140 [STRUT KIT] EDK06-K4474	[Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle.
MITSUBISHI GALANT FORTIS SPORTBACK CX4A 2000 cc / AWD			Ft: -50 Rr: -40	Ft: -60 to -40 Rr: -50 to -30	Ft: -94 to -38 Rr: -81 to -4		NOT Compatible	

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

**NEW PRODUCT GUIDE**



***STREET ADVANCE Damper Kit for New NOTE (E12)! Available Early April!  
HIGH.TECH Spring Kit is also Coming Soon!***

**STREET ADVANCE  
DAMPER**

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop (mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
NISSAN NOTE E12 1200 cc / FWD	GSK44-21AS2 JPY 101,000 JAN : 4582202758515	Ft: 4.0 Rr: 4.0	Ft: -40 Rr: -30	Ft: -50 to -30 Rr: -40 to -20	Ft: -60 to 0 Rr: -48 to -12	Early April	NOT Compatible	



\*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection. TEIN dampers are designed to comply with the regulations at the standard ride height drop.

**For product information, please contact:**  
 TEIN INC. Sales Section  
 Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123  
[http://www.tein.co.jp/global\\_en.html](http://www.tein.co.jp/global_en.html)  
 E-mail [os-inquiry@tein.co.jp](mailto:os-inquiry@tein.co.jp)

