NEW PRODUCT GUIDE



"MONO SPORT" for Nissan 180SX/Silvia (S13),

Skyline (PV36/KV36) & Fairlady (Z34) will be Available Soon!



BHIIIPER									
Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Setting	Set Spring (kgf/mm)	Ride Height Drop (mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
NISSAN 180SX KRPS13/RPS13 2000 cc / RWD	GSN20-71SS4 JPY 178,000 JAN: 4582202758973	SPORT	Ft : 10.0 Rr : 8.0	Ft : -50 Rr : -25	Ft:-60 to -40 Rr:-35 to -15	Ft: -96 to +4 Rr: -12 to +5	Early February	MOTOR KIT: EDK05-12140 STRUT KIT: EDK06-K4474	[Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed. Rr: Body panel might need to be modified (bent), if clearance between motor and body panel is insufficient. Interior needs to be cut or removed.
NISSAN 180SX KRS13/RS13 1800 cc / RWD	GSN20-71SS4 JPY 178,000 JAN: 4582202758973	SPORT	Ft : 10.0 Rr : 8.0	Ft : -50 Rr : -25	Ft:-60 to -40 Rr:-35 to -15	Ft: -96 to +4 Rr: -12 to +5	Early February	MOTOR KIT: EDK05-12140 STRUT KIT: EDK06-K4474	[Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed. Rr: Body panel might need to be modified (bent), if clearance between motor and body panel is insufficient. Interior needs to be cut or removed.
NISSAN SILVIA KPS13/PS13 2000 cc / RWD	GSN20-71SS4 JPY 178,000 JAN: 4582202758973	SPORT	Ft : 10.0 Rr : 8.0	Ft : -50 Rr : -25	Ft:-60 to -40 Rr:-35 to -15	Ft: -96 to +4 Rr: -12 to +5	Early February	MOTOR KIT: EDK05-12140 STRUT KIT: EDK06-K4474	[Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed. Rr: Body panel might need to be modified (bent), if clearance between motor and body panel is insufficient. Interior needs to be cut or removed.
NISSAN SILVIA S13 1800 cc / RWD	GSN20-71SS4 JPY 178,000 JAN: 4582202758973	SPORT	Ft : 10.0 Rr : 8.0	Ft : -50 Rr : -25	Ft:-60 to -40 Rr:-35 to -15	Ft: -96 to +4 Rr: -12 to +5	Early February	MOTOR KIT: EDK05-12140 STRUT KIT: EDK06-K4474	[Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed. Rr: Body panel might need to be modified (bent), if clearance between motor and body panel is insufficient. Interior needs to be cut or removed.
NISSAN SKYLINE PV36 3500 cc / RWD	GSP92-71AS3 JPY 158,000 JAN: 4582202759154	SPORT	Ft : 14.0 Rr : 12.0	Ft : -35 Rr : -40	Ft:-45 to -25 Rr:-50 to -40	Ft:-123 to -6 Rr:-79 to -38	Early February	MOTOR KIT: EDK05-12120	[Upon EDFC Installation] Ft: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Rr: Motor needs to be waterproofed with silicon sealant.
NISSAN SKYLINE KV36 3700 cc / RWD	GSP92-71AS3 JPY 158,000 JAN: 4582202759154	SPORT	Ft : 14.0 Rr : 12.0	Ft : -35 Rr : -35	Ft:-45 to -25 Rr:-45 to -30	Ft:-123 to -6 Rr:-69 to -27	Early February	MOTOR KIT: EDK05-12120	[Upon EDFC Installation] Ft: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Rr: Motor needs to be waterproofed with silicon sealant.
NISSAN FAIRLADY Z Z34 3700 cc / RWD	GSP92-71AS3 JPY 158,000 JAN: 4582202759154	SPORT	Ft : 14.0 Rr : 12.0	Ft : -25 Rr : -25	Ft: -35 to -15 Rr: -35 to -15	Ft:-113 to +4 Rr:-52 to -10	Early February	MOTOR KIT: EDK05-12120	[Upon EDFC Installation] Ft: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Rr: Motor needs to be waterproofed with silicon sealant.

^{*}For EDFC Series, Controller kit (sold separately) is required, in addition to Motor Kit etc noted in the chart.

For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection.

TEIN dampers are designed to comply with the regulations at the standard ride height drop.

For product information, please contact:

TEIN INC. Sales Section
Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123
Web http://www.tein.co.jp/global_en.html
E-mail os-inquiry@tein.co.jp



^{*}For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations.