

## High-Quality All-Round Model Shock Absorber for the Street

"STREET ADVANCE" will be released to the market, starting January 4th, 2012!

## STREET ADUANCE

Vehicle Make	Vehicle Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	EDFC Fitting	Remarks
ΤΟΥΟΤΑ	bB QNC20 1300cc / FWD	GSL96-21AS2 JPY101,000	Ft: I.D.70 4.0k 250mm	Ft: -60mm Rr: -50mm	Ft: -70 to -50 Rr: -60 to -45	Ft: -80 to -26 Rr: -65 to -45	NOT Compatible	
ΤΟΥΟΤΑ	bB QNC21 1500cc / FWD	JAN: 4582202756191	Rr: Exclusive Spring 2.8k	Ft: -60mm Rr: -50mm	Ft: -70 to -50 Rr: -60 to -45	Ft: -80 to -26 Rr: -65 to -45	NOT Compatible	
ΤΟΥΟΤΑ	ISIS ANM10W 2000cc / FWD	GSL76-21AS2 JPY103,000 JAN: 4582202756573	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 6.0k	Ft: -50mm Rr: -40mm	Ft: -60 to -40 Rr: -50 to -30	Ft: -70 to -33 Rr: -61 to -19	NOT Compatible	
ΤΟΥΟΤΑ	ARISTO JZS160 3000cc / RWD	GST76-21SS2 JPY88,000	Ft: Exclusive Spring 10.0k	Ft: -40mm Rr: -25mm	Ft: -50 to -30 Rr: -35 to -15	Ft: -58 to +17 Rr: -53 to -12	(M12-M12) EDK04-K4469	Spring Seat Position: Ft=-5mm, compared to JZS161. [Upon EDFC Installation] Rr: Interior needs to be modified or removed, if it interferes with motor.
ΤΟΥΟΤΑ	ARISTO JZS161 3000cc / RWD	JAN: 4582202756832	Rr: I.D.70-90 9.0k 225mm	Ft: -40mm Rr: -25mm	Ft: -50 to -30 Rr: -35 to -15	Ft: -63 to +12 Rr: -53 to -12	(Black) EDK04-P2756 (Silver)	[Upon EDFC Installation] Rr: Interior needs to be modified or removed, if it interferes with motor.
ΤΟΥΟΤΑ	ALTEZZA SXE10 2000cc / RWD	GSY20-21SS2 JPY86,000	Ft: I.D.70 8.0k 250mm Rr: I.D.70-90 6.0k 250mm	Ft: -30mm Rr: -25mm	Ft: -40 to -20 Rr: -35 to -15	Ft: -60 to +1 Rr: -55 to -13	NOT Compatible	
ΤΟΥΟΤΑ	ALTEZZA GXE10 2000cc / RWD	JAN: 4582202756207		Ft: -30mm Rr: -25mm	Ft: -40 to -20 Rr: -35 to -15	Ft: -60 to +1 Rr: -55 to -13	NOT Compatible	
τογοτά	ALPHARD / VELLFIRE ANH20W 2400cc / FWD	GSC78-21AS2 JPY105.000	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 6.0k	Ft: -50mm Rr: -45mm	Ft: -60 to -40 Rr: -55 to -35	Ft: -75 to -28 Rr: -63 to -20	(M12-M14)	Rr: OE dust boot needs to be modified. When adjusting Rr ride height, HAS needs to be removed once. Spring seat position: Ft=-5mm, compared to GGH20W. [Upon EDFC Installation] Service hole cover needs to be cut or removed. Motor needs to be installed parallel to the vehicle body. Need to take precaution when sliding 3rd-row seat, due to insufficient clearance with motor.
τογοτά	ALPHARD / VELLFIRE GGH20W 3500cc / FWD	JAN: 4582202756238		Ft: -55mm Rr: -50mm	Ft: -65 to -45 Rr: -60 to -40	Ft: -85 to -28 Rr: -68 to -25	(Silver)	Rr: OE dust boot needs to be modified. When adjusting Rr ride height, HAS needs to be removed once. [Upon EDFC Installation] Service hole cover needs to be cut or removed. Motor needs to be installed parallel to the vehicle body. Need to take precaution when sliding 3rd-row seat, due to insufficient clearance with motor. *EDEC cold separately: Motor Kit. JRV15 500 / Contempler Kit. JRV24 000



Vehicle Make	Vehicle Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	EDFC Fitting	Remarks
τογοτά	ALPHARD / VELLFIRE ANH25W 2400cc / AWD	GSC86-21AS2 JPY105.000	Ft: Exclusive Spring 5.0k Rr: Exclusive Spring 6.0k	Ft: -40mm Rr: -45mm	Ft: -50 to -30 Rr: -55 to -35	Ft: -60 to -15 Rr: -75 to -33	EDK05-12140 (M12-M14) EDK04-K4469	Rr: OE dust boot needs to be modified. When adjusting Rr ride height, HAS needs to be removed once. [Upon EDFC Installation] Service hole cover needs to be cut or removed. Motor needs to be installed parallel to the vehicle body. Need to take precaution when sliding 3rd-row seat, due to insufficient clearance with motor.
τογοτά	ALPHARD / VELLFIRE GGH25W 3500cc / AWD	JAN: 4582202756382		Ft: -40mm Rr: -45mm	Ft: -50 to -30 Rr: -55 to -40	Ft: -70 to -25 Rr: -83 to -40	(Black) EDK04-P2756 (Silver)	Rr: OE dust boot needs to be modified. When adjusting Rr ride height, HAS needs to be removed once. Spring Seat Position: Ft/Rr=+10/+6mm, compared to ANH25W. [Upon EDFC Installation] Service hole cover needs to be cut or removed. Motor needs to be installed parallel to the vehicle body. Need to take precaution when sliding 3rd-row seat, due to insufficient clearance with motor.
ΤΟΥΟΤΑ	WISH ZGE20G 1800cc / FWD	GSQ40-21SS2 JPY103,000 JAN: 4582202756740	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 5.0k	Ft: -45mm Rr: -40mm	Ft: -55 to -35 Rr: -50 to -30	Ft: -70 to -26 Rr: -70 to -3	NOT Compatible	Rr: Interior needs to be cut, to avoid interference.
ΤΟΥΟΤΑ	WISH ZGE20W 1800cc / FWD	GSQ04-21SS2 JPY103,000 JAN: 4582202756726	Ft: I.D.70-90 4.0k 250mm Rr: I.D.70-90 5.0k 250mm	Ft: -45mm Rr: -35mm	Ft: -55 to -35 Rr: -45 to -25	Ft: -70 to -35 Rr: -61 to -10	NOT Compatible	Rr: Interior needs to be cut, to avoid interference.
ΤΟΥΟΤΑ	VITZ KSP90 1000cc / FWD			Ft: -45mm Rr: -40mm	Ft: -55 to -35 Rr: -50 to -30	Ft: -65 to -29 Rr: -66 to -27	NOT Compatible	
ΤΟΥΟΤΑ	VITZ SCP90 1300cc / FWD	GSL70-21AS2 JPY101,000 JAN: 4582202756566	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 3.1k	Ft: -40mm Rr: -35mm	Ft: -50 to -30 Rr: -45 to -25	Ft: -60 to -24 Rr: -61 to -22	NOT Compatible	
ΤΟΥΟΤΑ	VITZ NCP91 1500cc / FWD			Ft: -35mm Rr: -35mm	Ft: -45 to -25 Rr: -45 to -25	Ft: -55 to -19 Rr: -61 to -22	NOT Compatible	
ΤΟΥΟΤΑ	VITZ NCP131 1500cc / FWD	GSQ32-21AS2 JPY101,000 JAN: 4582202756115	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 3.1k	Ft: -35mm Rr: -25mm	Ft: -45 to -25 Rr: -35 to -15	Ft: -50 to -20 Rr: -51 to -12	NOT Compatible	
ΤΟΥΟΤΑ	VOXY / NOAH ZRR70W 2000cc / FWD			Ft: -50mm Rr: -50mm	Ft: -60 to -40 Rr: -60 to -40	Ft: -80 to -23 Rr: -78 to -36	NOT Compatible	Rr: OE dust boot needs to be modified.
ΤΟΥΟΤΑ	VOXY / NOAH ZRR70W(G's) 2000cc / FWD	-		Ft: -10mm Rr: -5mm	Ft: -20 to 0 Rr: -15 to +5	Ft: -40 to +17 Rr: -33 to +9	NOT Compatible	Rr: OE dust boot needs to be modified.
ΤΟΥΟΤΑ	VOXY / NOAH ZRR70G 2000cc / FWD	GSC56-21AS2 JPY105,000 JAN: 4582202756214	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 6.0k	Ft: -50mm Rr: -50mm	Ft: -60 to -40 Rr: -60 to -40	Ft: -80 to -23 Rr: -78 to -36	NOT Compatible	Rr: OE dust boot needs to be modified.
ΤΟΥΟΤΑ	VOXY / NOAH ZRR75W 2000cc / AWD			Ft: -55mm Rr: -80mm	Ft: -65 to -45 Rr: -90 to -70	Ft: -85 to -28 Rr: -108 to -66	NOT Compatible	Rr: OE dust boot needs to be modified.
τογοτα	VOXY / NOAH ZRR75G 2000cc / AWD			Ft: -55mm Rr: -80mm	Ft: -65 to -45 Rr: -90 to -70	Ft: -85 to -28 Rr: -108 to -66	NOT Compatible	Rr: OE dust boot needs to be modified.



Vehicle Make	Vehicle Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	EDFC Fitting	Remarks
ΤΟΥΟΤΑ	ESTIMA ACR50W 2400cc / FWD	GSL98-21AS2 JPY105.000	Ft: Exclusive Spring 4.0k	Ft: -50mm Rr: -45mm	Ft: -60 to -40 Rr: -55 to -35	Ft: -84 to -16 Rr: -67 to -25	NOT Compatible	Rr: OE dust boot needs to be modified. When adjusting Rr ride height, HAS needs to be removed once.
ΤΟΥΟΤΑ	ESTIMA GSR50W 3500cc / FWD	JAN: 4582202756597	Rr: Exclusive Spring 6.0k	Ft: -50mm Rr: -50mm	Ft: -60 to -40 Rr: -60 to -40	Ft: -84 to -26 Rr: -72 to -30	NOT Compatible	Rr: OE dust boot needs to be modified. When adjusting Rr ride height, HAS needs to be removed once. Spring Seat Position: Ft=+10mm, compared to ACR50W.
ΤΟΥΟΤΑ	ESTIMA ACR55W 2400cc / AWD			Ft: -35mm Rr: -45mm	Ft: -45 to -25 Rr: -55 to -35	Ft: -50 to -15 Rr: -66 to -24	NOT Compatible	Rr: OE dust boot needs to be modified. When adjusting Rr ride height, HAS needs to be removed once.
ΤΟΥΟΤΑ	ESTIMA GSR55W 3500cc / AWD	GSC08-21AS2 JPY105,000 JAN: 4582202756368	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 6.0k	Ft: -45mm Rr: -60mm	Ft: -55 to -35 Rr: -70 to -50	Ft: -70 to -35 Rr: -81 to -39	NOT Compatible	Rr: OE dust boot needs to be modified. When adjusting Rr ride height, HAS needs to be removed once. Spring Seat Position: Ft=+10mm, compared to ACR55W.
ΤΟΥΟΤΑ	ESTIMA HYBRID AHR20W 2400cc / AWD			Ft: -50mm Rr: -60mm	Ft: -60 to -40 Rr: -70 to -50	Ft: -75 to -40 Rr: -81 to -39	NOT Compatible	Rr: OE dust boot needs to be modified. When adjusting Rr ride height, HAS needs to be removed once. Spring Seat Position: Ft=+10mm, compared to ACR55W.
ΤΟΥΟΤΑ	COROLLA RUMION ZRE152N 1800cc / FWD	GSQ12-21AS2 JPY105,000 JAN: 4582202756733	Ft: I.D.70 4.0k 250mm Rr: Exclusive Spring 3.5k	Ft: -25mm Rr: -40mm	Ft: -35 to -15 Rr: -50 to -30	Ft: -45 to -5 Rr: -62 to -29	NOT Compatible	
τογοτα	SUPRA JZA80 3000cc / RWD	GST60-21SS2		Ft: -20mm Rr: -20mm	Ft: -30 to -10 Rr: -30 to -10	Ft: -57 to +25 Rr: -55 to +6	(M12-M12) EDK04-K4469	NOT compatible with vehicle with REAS type shock absorber. [Upon EDFC Installation] Rr: Interior needs to be cut or removed, if it interferes.
ΤΟΥΟΤΑ	SOARER JZZ30 2500cc / RWD	GS160-215S2 JPY88,000 JAN: 4582202756818	Ft: Exclusive Spring 12.0k Rr: Exclusive Spring 7.0k	Ft: -20mm Rr: -30mm	Ft: -30 to -10 Rr: -40 to -25	Ft: -57 to +25 Rr: -86 to -25		To install the kit onto the vehicle equipped with TEMS, 'OE mount for the non-TEMS vehicle' is required. Spring seat position: Rr=+15mm, compared to JZA80. [Upon EDFC Installation] Rr: Cover above mount needs to be removed.
ΤΟΥΟΤΑ	PRIUS ZVW30 1800cc / FWD	GSQ08-21AS2 JPY105,000 JAN: 4582202756153	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 4.0k	Ft: -40mm Rr: -45mm	Ft: -50 to -30 Rr: -55 to -35	Ft: -61 to -6 Rr: -69 to -33	NOT Compatible	Exclusively for vehicles with floating (input-separation) type upper mounts on front. Reference Trim Level G, S Touring Selection. (Incl. G and/or S models equipped with moonroof)
ΤΟΥΟΤΑ	PRIUS ZVW30 1800cc / FWD	GSQ18-21AS2 JPY105,000 JAN: 4582202756146	Ft: I.D.70 4.0k 250mm Rr: Exclusive Spring 4.0k	Ft: -45mm Rr: -50mm	Ft: -55 to -35 Rr: -60 to -40	Ft: -66 to -26 Rr: -74 to -38	NOT Compatible	Exclusively for vehicles with ball bearing (concentrated-load) type upper mounts on front. Reference Trim Level G, S, L (excl. G and/or S models equipped with moonroof)
ΤΟΥΟΤΑ	PRIUS ALPHA ZVW40W 1800cc / FWD	GSQ44-21AS2 JPY105,000	Ft: Exclusive Spring 5.0k	Ft: -35mm Rr: -35mm	Ft: -45 to -25 Rr: -45 to -25	Ft: -70 to -23 Rr: -58 to -24	NOT Compatible	Spring Seat Position: Ft=+5mm, compared to ZVW41W.
ΤΟΥΟΤΑ	PRIUS ALPHA ZVW41W 1800cc / FWD	JAN: 4582202756757	Rr: Exclusive Spring 4.0k	Ft: -35mm Rr: -35mm	Ft: -45 to -25 Rr: -45 to -25	Ft: -65 to -18 Rr: -58 to -24	NOT Compatible	
ΤΟΥΟΤΑ	MARK II / VEROSSA JZX110 2500cc / RWD	GSY20-21SS2	Ft: I.D.70 8.0k 250mm	Ft: -50mm Rr: -40mm	Ft: -60 to -40 Rr: -50 to -30	Ft: -95 to -22 Rr: -78 to -36	NOT Confirmed	Spring Seat Position: Ft/Rr=+5/+5mm, compared to SXE10.
ΤΟΥΟΤΑ	MARK II BLIT JZX110W 2500cc / RWD	– JPY86,000 JAN: 4582202756207	Rr: I.D.70-90 6.0k 250mm	Ft: -50mm Rr: -40mm	Ft: -60 to -40 Rr: -50 to -30	Ft: -88 to -13 Rr: -75 to -33	NOT Confirmed	Spring Seat Position: Ft/Rr=+1/+3mm, compared to SXE10.
τογοτα	MARK X ZIO ANA10 2400cc / FWD	GSQ10-21AS2 JPY105,000 JAN: 4582202756221	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 6.5k	Ft: -45mm Rr: -25mm	Ft: -55 to -35 Rr: -35 to -15	Ft: -75 to -24 Rr: -50 to -10	NOT Compatible	



Vehicle Make	Vehicle Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	EDFC Fitting	Remarks
ΤΟΥΟΤΑ	RACTIS NCP120 1500cc / FWD	GSQ32-21AS2 JPY101,000 JAN: 4582202756115	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 3.1k	Ft: -40mm Rr: -40mm	Ft: -50 to -30 Rr: -50 to -30	Ft: -55 to -25 Rr: -66 to -27	NOT Compatible	
NISSAN	CUBE Z12 1500cc / FWD	GSK06-21AS2 JPY101,000 JAN: 4582202756511	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 5.2k	Ft: -40mm Rr: -35mm	Ft: -50 to -30 Rr: -45 to -25	Ft: -60 to -13 Rr: -63 to -12	NOT Compatible	
NISSAN	JUKE YF15 1500cc / FWD	GSK22-21AS2 JPY101,000 JAN: 4582202756535	Ft: Exclusive Spring 4.0k Rr: Exclusive Spring 4.1k	Ft: -45mm Rr: -45mm	Ft: -55 to -35 Rr: -55 to -35	Ft: -65 to -17 Rr: -60 to -18	NOT Compatible	
NISSAN	SILVIA S15 2000cc / RWD	GSN52-21SS2 JPY103,000 JAN: 4582202756689	Ft: I.D.70 5.0k 225mm Rr: I.D.70 4.0k 250mm	Ft: -20mm Rr: -15mm	Ft: -30 to -10 Rr: -25 to -5	Ft: -50 to -4 Rr: -35 to +5	NOT Compatible	
NISSAN	SERENA C26 2000cc / FWD	GSK28-21AS2 JPY105.000	Ft: Exclusive Spring 5.0k	Ft: -50mm Rr: -40mm	Ft: -60 to -40 Rr: -50 to -35	Ft: -70 to -39 Rr: -63 to -35	NOT Compatible	
NISSAN	SERENA FC26 2000cc / FWD	JAN: 4582202756542	Rr: Exclusive Spring 7.0k	Ft: -45mm Rr: -40mm	Ft: -55 to -35 Rr: -50 to -35	Ft: -65 to -34 Rr: -63 to -35	NOT Compatible	
MAZDA	AZ-WAGON MJ23S 660cc / AWD	GSU74-21AS2 JPY99,000 JAN: 4582202756863	Ft: I.D.70 4.0k 200mm Rr: Exclusive Spring 2.0k	Ft: -40mm Rr: -35mm	Ft: -50 to -30 Rr: -44 to -28	Ft: -60 to -30 Rr: -44 to -28	NOT Compatible	
MAZDA	AXELA SPORT BLEFW 2000cc / FWD		Ft: I.D.70 5.0k 225mm Rr: Exclusive Spring 4.0k	Ft: -35mm Rr: -35mm	Ft: -40 to -25 Rr: -40 to -25	Ft: -59 to -23 Rr: -51 to -23		[Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Motor and its joint part need to be waterproofed with silicon sealant. Motor needs to be installed facing forwards.
MAZDA	AXELA SEDAN BLEFP 2000cc / FWD	GSM08-21452		Ft: -35mm Rr: -35mm	Ft: -40 to -25 Rr: -40 to -25	Ft: -59 to -23 Rr: -51 to -23	EDK05-12120 (M12-M12) EDK04-K4469 (Black) EDK04-P2756 (Silver)	[Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Motor and its joint part need to be waterproofed with silicon sealant. Motor needs to be installed facing forwards.
MAZDA	MAZDASPEED AXELA BL3FW 2300cc / FWD	GSM98-21AS2 JPY105,000 JAN: 4582202756641		Ft: -35mm Rr: -25mm	Ft: -40 to -35 Rr: -35 to -18	Ft: -64 to -28 Rr: -46 to -18		Spring Seat Position: Ft/Rr=+5/+4mm, compared to BLEFW. When using OE tire/wheel size: Ft: If lowering below recommended ride height range, spring seat may interfere with tire. Please check and make sure there is no interference when adjusting ride height. *Recommended tire/wheel size* Tire: 225/40-18, Wheel: 18x7.5J inset less than 48 [Upon EDFC Installation] Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Motor and its joint part need to be waterproofed with silicon sealant. Motor needs to be installed facing forwards.
MAZDA	DEMIO DE3FS 1300cc / FWD	GSM90-21AS2 JPY101.000	Ft: Exclusive Spring 2.5k Rr: Exclusive Spring 1.9k	Ft: -40mm Rr: -50mm	Ft: -50 to -30 Rr: -60 to -40	Ft: -60 to -25 Rr: -70 to -40	NOT Compatible	
MAZDA	DEMIO DE5FS 1500cc / FWD	JAN: 4582202756634		Ft: -45mm Rr: -40mm	Ft: -55 to -35 Rr: -50 to -30	Ft: -65 to -30 Rr: -60 to -30	NOT Compatible	*EDEC oold opportely: Mater Vit. IDVAE 500 / Conterplier Vit. IDV24 000



Vehicle Make	Vehicle Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	EDFC Fitting	Remarks
MAZDA	ROADSTER NA6CE 1600cc / RWD			Ft: -35mm Rr: -40mm	Ft: -45 to -25 Rr: -50 to -30	Ft: -61 to -1 Rr: -66 to -8	EDK05-10100	Rr: Spare tire needs to be relocated and anchored, to avoid interference with Rr shaft top. OE mount needs to be modified with included file. Spring Seat Position: Ft/Rr=-16/-16mm, compared to NB8C. May not be lowered well depending on vehicle Trim Level and/or weight. [Upon EDFC Installation] Ft: Left side connector (on vehicle side) needs to be relocated, if it interferes. Rr: Spare tire needs to be relocated.
MAZDA	ROADSTER NA8C 1800cc / RWD	GSM40-21SS2 JPY86,000 JAN: 4582202756627	Ft: I.D.70 6.0k 200mm Rr: I.D.70 5.0k 200mm	Ft: -40mm Rr: -50mm	Ft: -50 to -30 Rr: -60 to -40	Ft: -66 to -8 Rr: -76 to -18	(M10-M10) EDK04-K4469 (Black) EDK04-P2756 (Silver)	Rr: Spare tire needs to be relocated and anchored, to avoid interference with Rr shaft top. OE mount needs to be modified with included file. Spring Seat Position: Ft/Rr=-16/-16mm, compared to NB8C. May not be lowered well depending on vehicle Trim Level and/or weight. [Upon EDFC Installation] Ft: Left side connector (on vehicle side) needs to be relocated, if it interferes. Rr: Spare tire needs to be relocated.
MAZDA	ROADSTER NB8C 1800cc / RWD			Ft: -20mm Rr: -40mm	Ft: -30 to -10 Rr: -50 to -30	Ft: -69 to +14 Rr: -89 to -8		[Upon EDFC Installation] Ft: Left side connector (on vehicle side) needs to be relocated, if it interferes. Rr: Interior needs to be modified or removed, if it interferes with motor.
HONDA	CR-Z ZF1 1500cc / FWD	GSHA6-21AS2 JPY101,000 JAN: 4582202756122	Ft: I.D.70 3.0k 250mm Rr: Exclusive Spring 4.0k	Ft: -40mm Rr: -40mm	Ft: -50 to -30 Rr: -50 to -30	Ft: -60 to -25 Rr: -59 to -16	NOT Compatible	
HONDA	ACCORD EURO-R CL7 2000cc / FWD	GSB48-21SS2 JPY88,000	Ft: I.D.70 8.0k 225mm	Ft: -50mm Rr: -30mm	Ft: -60 to -40 Rr: -40 to -20	Ft: -90 to -42 Rr: -56 to -14	NOT Compatible	Ft: Use the anti-loose bracket from OE shock absorber. Applicable to vehicles with auto head-light leveling function.
HONDA	ACCORD CL9 2400cc / FWD	JAN: 4582202756313	Rr: I.D.70 4.0k 250mm	Ft: -40mm Rr: -30mm	Ft: -50 to -30 Rr: -40 to -20	Ft: -80 to -32 Rr: -56 to -14	NOT Compatible	Ft: Use the anti-loose bracket from OE shock absorber. Applicable to vehicles with auto head-light leveling function.
HONDA	INSIGHT ZE2 1300cc / FWD	GSB94-21AS2 JPY105,000 JAN: 4582202756351	Ft: Exclusive Spring 3.0k Rr: Exclusive Spring 4.0k	Ft: -40mm Rr: -45mm	Ft: -50 to -30 Rr: -55 to -35	Ft: -64 to -30 Rr: -62 to -29	NOT Compatible	
HONDA	ELYSION RR1 2400cc / FWD			Ft: -45mm Rr: -35mm	Ft: -55 to -35 Rr: -45 to -25	Ft: -75 to -23 Rr: -61 to -15		[Upon EDFC Installation] Rr: Service hole cover needs to be removed, and side cover for 3rd-row seat needs to be removed or modified. Needs to take precaution when sliding 3rd-row seat, as motor is mounted close to the cushioning.
HONDA	ELYSION RR2 2400cc / AWD	GSA94-21AS2		Ft: -65mm Rr: -60mm	Ft: -75 to -55 Rr: -70 to -50	Ft: -95 to -43 Rr: -86 to -40	EDK05-10100 (M10-M10)	[Upon EDFC Installation] Rr: Service hole cover needs to be removed, and side cover for 3rd-row seat needs to be removed or modified. Needs to take precaution when sliding 3rd-row seat, as motor is mounted close to the cushioning.
HONDA	ELYSION RR3 3000cc / FWD	JPY101,000 JAN: 4582202756283	Ft: I.D.70 10.0k 250mm Rr: Exclusive Spring 11.0k	Ft: -55mm Rr: -30mm	Ft: -65 to -45 Rr: -40 to -20	Ft: -92 to -41 Rr: -56 to -10	EDK04-K4469 (Black) EDK04-P2756 (Silver)	Spring Seat Position: Ft=+5mm, compared to RR1. [Upon EDFC Installation] Rr: Service hole cover needs to be removed, and side cover for 3rd-row seat needs to be removed or modified. Needs to take precaution when sliding 3rd-row seat, as motor is mounted close to the cushioning.
HONDA	ELYSION RR4 3000cc / AWD			Ft: -60mm Rr: -50mm	Ft: -70 to -50 Rr: -60 to -40	Ft: -102 to -50 Rr: -80 to -34		Spring Seat Position: Ft/Rr=+8/+2mm, compared to RR1. [Upon EDFC Installation] Rr: Service hole cover needs to be removed, and side cover for 3rd-row seat needs to be removed or modified. Needs to take precaution when sliding 3rd-row seat, as motor is mounted close to the cushioning. *EDEC sold soparately: Meter Kit: IBY15 500 / Contoroller Kit: IBY24 000



Vehicle Make	Vehicle Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	EDFC Fitting	Remarks
HONDA	ELYSION PRESTIGE RR1 2400cc / FWD			Ft: -40mm Rr: -30mm	Ft: -50 to -30 Rr: -40 to -20	Ft: -70 to -18 Rr: -56 to -10		[Upon EDFC Installation] Rr: Service hole cover needs to be removed, and side cover for 3rd-row seat needs to be removed or modified. Needs to take precaution when sliding 3rd-row seat, as motor is mounted close to the cushioning.
HONDA	ELYSION PRESTIGE RR5 3500cc / FWD	GSA94-21AS2 JPY101,000 JAN: 4582202756283	Ft: I.D.70 10.0k 250mm Rr: Exclusive Spring 11.0k	Ft: -60mm Rr: -35mm	Ft: -70 to -50 Rr: -45 to -25	Ft: -102 to -46 Rr: -61 to -15	(M10-M10)	Spring Seat Position: Ft=+5mm, compared to RR1. [Upon EDFC Installation] Rr: Service hole cover needs to be removed, and side cover for 3rd-row seat needs to be removed or modified. Needs to take precaution when sliding 3rd-row seat, as motor is mounted close to the cushioning.
HONDA	ELYSION PRESTIGE RR6 3500cc / AWD			Ft: -60mm Rr: -50mm	Ft: -70 to -50 Rr: -60 to -40	Ft: -102 to -46 Rr: -76 to -30		Spring Seat Position: Ft=+5mm, compared to RR1. [Upon EDFC Installation] Rr: Service hole cover needs to be removed, and side cover for 3rd-row seat needs to be removed or modified. Needs to take precaution when sliding 3rd-row seat, as motor is mounted close to the cushioning.
HONDA	ODYSSEY RA6 2300cc / FWD			Ft: -55mm Rr: -60mm	Ft: -65 to -45 Rr: -70 to -50	Ft: -100 to -27 Rr: -87 to -33		[Upon EDFC Installation] Rr: NOT compatible with vehicle which has automatic air conditioner line on right side. Interior needs to be cut, to avoid interference.
HONDA	ODYSSEY RA6 (ABSOLUTE) 2300cc / FWD		Ft: I.D.70 10.0k 250mm Rr: Exclusive Spring 8.8k	Ft: -40mm Rr: -45mm	Ft: -50 to -30 Rr: -55 to -35	Ft: -85 to -12 Rr: -72 to -18	EDK05-10100 (M10-M10) EDK04-K4469 (Black) EDK04-P2756 (Silver)	Data applies to ABSOLUTE model. [Upon EDFC Installation] Rr: NOT compatible with vehicle which has automatic air conditioner line on right side. Interior needs to be cut, to avoid interference.
HONDA	ODYSSEY RA8 3000cc / FWD	GSH78-21AS2 JPY101,000 JAN: 4582202756474		Ft: -50mm Rr: -45mm	Ft: -60 to -40 Rr: -55 to -35	Ft: -103 to -30 Rr: -72 to -18		Spring Seat Position: Ft=+5mm, compared to RA6. [Upon EDFC Installation] Rr: NOT compatible with vehicle which has automatic air conditioner line on right side. Interior needs to be cut, to avoid interference.
HONDA	ODYSSEY RA8 (ABSOLUTE) 3000cc / FWD			Ft: -35mm Rr: -30mm	Ft: -45 to -25 Rr: -40 to -20	Ft: -88 to -15 Rr: -57 to -3		Spring Seat Position: Ft=+5mm, compared to RA6. Data applies to ABSOLUTE model. [Upon EDFC Installation] Rr: NOT compatible with vehicle which has automatic air conditioner line on right side. Interior needs to be cut, to avoid interference.
HONDA	ODYSSEY RB1 2400cc / FWD	GSA70-21SS2 JPY83,000 JAN: 4582202756276	Ft: I.D.70 10.0k 250mm Rr: I.D.70 10.0k 200mm	Ft: -50mm Rr: -45mm	Ft: -60 to -40 Rr: -55 to -35	Ft: -80 to -25 Rr: -83 to -33	NOT Compatible	Ft: Use the anti-loose bracket from OE shock absorber. Rr: Interior needs to be removed upon damping force adjustment.
HONDA	ODYSSEY RB3 2400cc / FWD	GSB84-21SS2 JPY83,000 JAN: 4582202756337	Ft: I.D.70 10.0k 250mm Rr: I.D.70 10.0k 200mm	Ft: -40mm Rr: -40mm	Ft: -50 to -30 Rr: -50 to -30	Ft: -70 to -11 Rr: -78 to -10	NOT Compatible	Ft: Use the anti-loose bracket from OE shock absorber. Rr: Interior needs to be removed upon damping force adjustment.
HONDA	STEP WGN RF3 2000cc / FWD			Ft: -55mm Rr: -50mm	Ft: -65 to -45 Rr: -60 to -40	Ft: -75 to -45 Rr: -74 to -26	NOT Compatible	
HONDA	STEP WGN RF5 2000cc / FWD	GSH90-21AS2 JPY103,000 JAN: 4582202756481	Ft: I.D.70 6.0k 250mm Rr: Exclusive Spring 6.9k	Ft: -60mm Rr: -45mm	Ft: -70 to -50 Rr: -55 to -35	Ft: -80 to -50 Rr: -69 to -21	NOT Compatible	
HONDA	STEP WGN RF7 2400cc / FWD			Ft: -55mm Rr: -50mm	Ft: -65 to -50 Rr: -60 to -40	Ft: -80 to -50 Rr: -79 to -31	NOT Compatible	Spring Seat Position: Ft/Rr=+5/+3mm, compared to RF3.



Vehicle Make	Vehicle Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	EDFC Fitting	Remarks
HONDA	STEP WGN RG1 2000cc / FWD	GSB18-21AS2 JPY105,000	Ft: Exclusive Spring 4.0k	Ft: -35mm Rr: -40mm	Ft: -45 to -25 Rr: -50 to -34	Ft: -60 to -25 Rr: -69 to -34	NOT Compatible	
HONDA	STEP WGN RG3 2400cc / FWD	JAN: 4582202756290	Rr: Exclusive Spring 3.3k	Ft: -30mm Rr: -40mm	Ft: -40 to -20 Rr: -50 to -34	Ft: -55 to -20 Rr: -69 to -34	NOT Compatible	
HONDA	STEP WGN RK1 2000cc / FWD	GSB98-21AS2 JPY105,000	Ft: Exclusive Spring 5.0k	Ft: -60mm Rr: -50mm	Ft: -70 to -50 Rr: -60 to -40	Ft: -85 to -34 Rr: -72 to -39	NOT Compatible	
HONDA	STEP WGN SPADA RK5 2000cc / FWD	JAN: 4582202756139	Rr: Exclusive Spring 6.0k	Ft: -55mm Rr: -50mm	Ft: -65 to -45 Rr: -60 to -40	Ft: -80 to -29 Rr: -72 to -39	NOT Compatible	
HONDA	STREAM RN6 1800cc / FWD	GSB38-21SS2 JPY103,000	Ft: Exclusive Spring 3.0k	Ft: -25mm Rr: -25mm	Ft: -35 to -15 Rr: -35 to -15	Ft: -45 to -7 Rr: -53 to +12	NOT Compatible	
HONDA	STREAM RN8 2000cc / FWD	JAN: 4582202756306	Rr: I.D.70 6.0k 225mm	Ft: -25mm Rr: -20mm	Ft: -35 to -15 Rr: -30 to -10	Ft: -50 to -12 Rr: -48 to +17	NOT Compatible	Spring Seat Position: Ft=+5mm, compared to RN6.
HONDA	FIT GD1 1300cc / FWD	GSA04-21AS2	1,000 Ft: I.D.70 4.0k 225mm	Ft: -45mm Rr: -20mm	Ft: -55 to -35 Rr: -30 to -10	Ft: -65 to -24 Rr: -41 to +1	EDK05-10120 (M10-M12) EDK04-K4469 (Black) EDK04-P2756 (Silver)	Rr: Service hole cover needs to be removed or cut. [Upon EDFC Installation] Ft: Bulkhead cover needs to be cut. Rr: Cover above mount needs to be removed. Motor needs to be installed parallel to the interior. Rear seat position needs to be set at a position that does not interfere with EDFC motor.
HONDA	FIT GD3 1500cc / FWD	– JPY101,000 JAN: 4582202756252		Ft: -55mm Rr: -30mm	Ft: -65 to -45 Rr: -40 to -20	Ft: -75 to -34 Rr: -51 to -9		Rr: Service hole cover needs to be removed or cut. [Upon EDFC Installation] Ft: Bulkhead cover needs to be cut. Rr: Cover above mount needs to be removed. Motor needs to be installed parallel to the interior. Rear seat position needs to be set at a position that does not interfere with EDFC motor.
HONDA	FIT GE6 1300cc / FWD			Ft: -45mm Rr: -45mm	Ft: -55 to -35 Rr: -55 to -35	Ft: -71 to -31 Rr: -71 to -31	NOT Compatible	Rr: Interior service hole cover needs to be removed or modified.
HONDA	FIT GE8 1500cc / FWD	GSB80-21AS2 JPY101,000 JAN: 4582202756177	Ft: Exclusive Spring 3.0k Rr: Exclusive Spring 2.0k	Ft: -30mm Rr: -30mm	Ft: -40 to -20 Rr: -40 to -20	Ft: -56 to -16 Rr: -56 to -16	NOT Compatible	Rr: Interior service hole cover needs to be removed or modified.
HONDA	FIT HYBRID GP1 1300cc / FWD			Ft: -30mm Rr: -30mm	Ft: -40 to -20 Rr: -40 to -30	Ft: -56 to -16 Rr: -70 to -30	NOT Compatible	Rr: Interior service hole cover needs to be removed or modified. Spring Seat Position: Rr=+9mm, compared to GE8.
HONDA	FIT SHUTTLE HYBRID GP2 1300cc / FWD	GSHB8-21AS2 JPY101,000 JAN: 4582202756986	Ft: Exclusive Spring 3.0k Rr: Exclusive Spring 4.0k	Ft: -40mm Rr: -40mm	Ft: -50 to -30 Rr: -50 to -30	Ft: -60 to -19 Rr: -54 to -14	NOT Compatible	
HONDA	FREED GB3 1500cc / FWD	GSB86-21AS2 JPY103,000	Ft: I.D.70 3.0k 250mm Rr: Exclusive Spring 4.2k	Ft: -45mm Rr: -40mm	Ft: -55 to -35 Rr: -50 to -30	Ft: -72 to -35 Rr: -62 to -29	NOT Compatible	Rr: Interior needs to be cut, to avoid interference.
HONDA	FREED SPIKE GB3 1500cc / FWD	JAN: 4582202756344		Ft: -40mm Rr: -40mm	Ft: -50 to -30 Rr: -50 to -30	Ft: -67 to -30 Rr: -62 to -29	NOT Compatible	



Vehicle Make	Vehicle Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	EDFC Fitting	Remarks
MITSUBISHI	LANCER EVOLUTION VII / VIII / IX CT9A 2000cc / AWD	GSR52-21SS2 JPY103,000	Ft: I.D.70 6.0k 250mm	Ft: -40mm Rr: -15mm	Ft: -50 to -30 Rr: -25 to -5	Ft: -62 to -28 Rr: -44 to +3	NOT Compatible	
MITSUBISHI	LANCER EVOLUTION WAGON CT9W 2000cc / AWD	JAN: 4582202756061	Rr: I.D.65 6.0k 225mm	Ft: -40mm Rr: -10mm	Ft: -50 to -30 Rr: -20 to 0	Ft: -52 to -18 Rr: -44 to +3	NOT Compatible	Spring Seat Position: Ft/Rr=-10/+5mm, compared to CT9A.
MITSUBISHI	LANCER EVOLUTION X CZ4A 2000cc / AWD	GSE18-21SS2 JPY103,000 JAN: 4582202756016	Ft: I.D.70 5.0k 225mm Rr: I.D.70 4.0k 250mm	Ft: -40mm Rr: -25mm	Ft: -50 to -30 Rr: -35 to -15	Ft: -62 to -28 Rr: -65 to -14	NOT Compatible	Rr: Shock absorber needs to be detached from vehicle, when adjusting damping force.
SUBARU	IMPREZA GDA 2000cc / AWD	GSS28-21SS2 JPY103,000	Ft: I.D.70 5.0k 225mm	Ft: -40mm Rr: -25mm	Ft: -50 to -30 Rr: -35 to -15	Ft: -65 to -24 Rr: -52 to -2	NOT Compatible	
SUBARU	IMPREZA GDB 2000cc / AWD	JAN: 4582202756085	Rr: I.D.70 4.0k 200mm	Ft: -40mm Rr: -25mm	Ft: -50 to -30 Rr: -35 to -15	Ft: -65 to -24 Rr: -52 to -2	NOT Compatible	Exclusively for type A thru D (Oct 00 - Jun 04).
SUBARU	IMPREZA GDB(E) 2000cc / AWD	GSS64-21SS2 JPY103,000 JAN: 4582202756078	Ft: I.D.70 5.0k 225mm Rr: I.D.70 4.0k 225mm	Ft: -40mm Rr: -25mm	Ft: -50 to -30 Rr: -35 to -15	Ft: -65 to -9 Rr: -55 to +5	NOT Compatible	For Type E or later (Jun 04+ / PCD=114.3).
SUBARU	IMPREZA GH3 1500cc / AWD			Ft: -25mm Rr: -30mm	Ft: -35 to -15 Rr: -40 to -20	Ft: -60 to +2 Rr: -66 to +14	NOT Compatible	
SUBARU	IMPREZA GH7 2000cc / AWD	GSS76-21SS2 JPY103,000 JAN: 4582202755996	Ft: I.D.70 5.0k 250mm Rr: Exclusive Spring 4.0k	Ft: -35mm Rr: -35mm	Ft: -45 to -25 Rr: -45 to -25	Ft: -70 to -8 Rr: -71 to +9	NOT Compatible	
SUBARU	IMPREZA GH8 2000cc / AWD			Ft: -35mm Rr: -35mm	Ft: -45 to -25 Rr: -45 to -25	Ft: -70 to -8 Rr: -71 to +9	NOT Compatible	
SUBARU	IMPREZA GRB 2000cc / AWD			Ft: -30mm Rr: -25mm	Ft: -40 to -20 Rr: -35 to -15	Ft: -60 to -15 Rr: -65 to +16	NOT Compatible	
SUBARU	IMPREZA GRF 2500cc / AWD	GSS78-21SS2	Ft: I.D.70 5.0k 250mm	Ft: -25mm Rr: -25mm	Ft: -35 to -15 Rr: -35 to -15	Ft: -55 to -10 Rr: -65 to +16	NOT Compatible	
SUBARU	IMPREZA GVB 2000cc / AWD	JPY103,000 JAN: 4582202756009	Rr: Exclusive Spring 4.0k	Ft: -30mm Rr: -15mm	Ft: -40 to -20 Rr: -25 to -5	Ft: -60 to -15 Rr: -55 to +26	NOT Compatible	
SUBARU	IMPREZA GVF 2500cc / AWD			Ft: -30mm Rr: -20mm	Ft: -40 to -20 Rr: -30 to -10	Ft: -60 to -15 Rr: -60 to +21	NOT Compatible	
SUBARU	FORESTER SH5 2000cc / AWD	GSS94-21SS2 JPY103,000 JAN: 4582202756801	Ft: Exclusive Spring 5.0k Rr: Exclusive Spring 4.0k	Ft: -50mm Rr: -50mm	Ft: -60 to -40 Rr: -60 to -40	Ft: -75 to -24 Rr: -80 to -28	NOT Compatible	
SUBARU	FORESTER SH9 2500cc / AWD			Ft: -55mm Rr: -50mm	Ft: -65 to -45 Rr: -60 to -40	Ft: -80 to -29 Rr: -80 to -28	NOT Compatible	
SUBARU	LUCRA / LUCRA CUSTOM L455F 660cc / FWD	GSD52-21AS2 JPY99,000 JAN: 4582202756429	Ft: I.D.70 5.0k 200mm Rr: Exclusive Spring 2.4k	Ft: -60mm Rr: -55mm	Ft: -70 to -50 Rr: -65 to -45	Ft: -80 to -29 Rr: -77 to -45	NOT Compatible	For vehicles with fog lights, if the position of the fog light is less than 250mm from the ground, it may not comply with vehicle safety regulations. Please adjust ride height so the distance is over 250mm.



Vehicle Make	Vehicle Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	EDFC Fitting	Remarks
SUZUKI	SWIFT ZC11S 1300cc / FWD			Ft: -20mm Rr: -25mm	Ft: -30 to -10 Rr: -35 to -15	Ft: -40 to +2 Rr: -38 to -10		[Upon EDFC Installation] Ft: Cowl top cover needs to be modified. Rr: Interior needs to be modified or removed, if it interferes with motor.
SUZUKI	SWIFT ZD11S 1300cc / AWD			Ft: -35mm Rr: -45mm	Ft: -45 to -25 Rr: -55 to -35	Ft: -60 to -18 Rr: -63 to -35	EDK05-10120	Spring Seat Position: Ft/Rr=+5/+5mm, compared to ZC21S. [Upon EDFC Installation] Ft: Cowl top cover needs to be modified. Rr: Interior needs to be modified or removed, if it interferes with motor.
SUZUKI	SWIFT ZC21S 1500cc / FWD	GSU46-21AS2 JPY101,000 JAN: 4582202756856	Ft: Exclusive Spring 3.0k Rr: Exclusive Spring 3.2k	Ft: -25mm Rr: -25mm	Ft: -35 to -15 Rr: -35 to -15	Ft: -45 to -3 Rr: -38 to -10	EDK04-P2756	[Upon EDFC Installation] Ft: Cowl top cover needs to be modified. Rr: Interior needs to be modified or removed, if it interferes with motor.
SUZUKI	SWIFT ZD21S 1500cc / AWD	1		Ft: -30mm Rr: -45mm	Ft: -40 to -20 Rr: -55 to -35	Ft: -55 to -13 Rr: -63 to -35	(Silver)	Spring Seat Position: Ft/Rr+5/+5mm, compared to ZC21S. [Upon EDFC Installation] Ft: Cowl top cover needs to be modified. Rr: Interior needs to be modified or removed, if it interferes with motor.
SUZUKI	SWIFT ZC71S 1200cc / FWD			Ft: -30mm Rr: -25mm	Ft: -40 to -20 Rr: -35 to -15	Ft: -50 to -8 Rr: -38 to -10		[Upon EDFC Installation] Ft: Cowl top cover needs to be modified. Rr: Interior needs to be modified or removed, if it interferes with motor.
SUZUKI	SWIFT ZC72S 1200cc / FWD	GSU82-21AS2 JPY101,000 JAN: 4582202756870	Ft: Exclusive Spring 3.0k Rr: Exclusive Spring 3.2k	Ft: -35mm Rr: -35mm	Ft: -45 to -25 Rr: -45 to -25	Ft: -60 to -22 Rr: -56 to -14	EDK05-10120 (M10-M12) EDK04-K4469 (Black) EDK04-P2756 (Silver)	[Upon EDFC Installation] Rr: Service hole cover needs to be cut or removed.
SUZUKI	SWIFT SPORT ZC31S 1600cc / FWD	GSU46-21AS2 JPY101,000 JAN: 4582202756856	Ft: Exclusive Spring 3.0k Rr: Exclusive Spring 3.2k	Ft: -45mm Rr: -30mm	Ft: -55 to -35 Rr: -40 to -20	Ft: -65 to -23 Rr: -48 to -20	EDK04-K4469 (Black)	Spring Seat Position: Rr=+5mm, compared to ZC21S. [Upon EDFC Installation] Ft: Cowl top cover needs to be modified. Rr: Interior needs to be modified or removed, if it interferes with motor.
SUZUKI	SPLASH XB32S 1200cc / FWD			Ft: -20mm Rr: -30mm	Ft: -30 to -10 Rr: -40 to -20	Ft: -40 to +2 Rr: -43 to -15	NOT Compatible	
SUZUKI	LAPIN HE22S 660cc / FWD	GSU74-21AS2	Ft: I.D.70 4.0k 200mm Rr: Exclusive Spring 2.0k	Ft: -45mm Rr: -30mm	Ft: -55 to -35 Rr: -39 to -23	Ft: -65 to -35 Rr: -39 to -23	NOT Compatible	
SUZUKI	LAPIN HE22S 660cc / AWD	JPY99,000 JAN: 4582202756863		Ft: -35mm Rr: -40mm	Ft: -45 to -25 Rr: -44 to -30	Ft: -55 to -25 Rr: -44 to -28	NOT Compatible	Spring Seat Position: Rr=-8mm, compared to FWD model.
SUZUKI	LANDY SC26 2000cc / FWD	GSK28-21AS2 JPY105,000 JAN: 4582202756542	Ft: Exclusive Spring 5.0k Rr: Exclusive Spring 7.0k	Ft: -50mm Rr: -40mm	Ft: -60 to -40 Rr: -50 to -35	Ft: -70 to -39 Rr: -63 to -35	NOT Compatible	



Vehicle Make	Vehicle Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	EDFC Fitting	Remarks
SUZUKI	WAGON R / WAGON R STINGRAY MH23S 660cc / FWD	GSU74-21AS2 JPY99.000	Ft: I.D.70 4.0k 200mm	Ft: -40mm Rr: -45mm	Ft: -50 to -30 Rr: -54 to -38	Ft: -60 to -30 Rr: -54 to -38	NOT Compatible	
SUZUKI	WAGON R / WAGON R STINGRAY MH23S 660cc / AWD	JAN: 4582202756863	Rr: Exclusive Spring 2.0k	Ft: -30mm Rr: -40mm	Ft: -40 to -25 Rr: -49 to -33	Ft: -55 to -25 Rr: -49 to -33	NOT Compatible	Spring Seat Position: Ft=+5mm, compared to FWD model.
DAIHATSU	TANTO / TANTO CUSTOM L375S 660cc / FWD	GSD48-21AS2 JPY99,000 JAN: 4582202756412	Ft: I.D.70 3.0k 225mm Rr: Exclusive Spring 2.6k	Ft: -40mm Rr: -25mm	Ft: -50 to -30 Rr: -35 to -15	Ft: -70 to -31 Rr: -47 to -14	NOT Compatible	For vehicles with fog lights, if the position of the fog light is less than 250mm from the ground, it may not comply with vehicle safety regulations. Please adjust ride height so the distance is over 250mm. Rr: Due to individual differences, interior needs to be cut or removed if interferes.
DAIHATSU	TANTO EXE / TANTO EXE CUSTOM L455S 660cc / FWD	GSD52-21AS2 JPY99,000 JAN: 4582202756429	Ft: I.D.70 5.0k 200mm Rr: Exclusive Spring 2.4k	Ft: -60mm Rr: -55mm	Ft: -70 to -50 Rr: -65 to -45	Ft: -80 to -29 Rr: -77 to -45		For vehicles with fog lights, if the position of the fog light is less than 250mm from the ground, it may not comply with vehicle safety regulations. Please adjust ride height so the distance is over 250mm.
DAIHATSU	MOVE / MOVE CUSTOM L175S 660cc / FWD	GSD36-21AS2 JPY99,000 JAN: 4582202756405	Ft: I.D.70 3.0k 225mm Rr: Exclusive Spring 2.4k	Ft: -35mm Rr: -25mm	Ft: -45 to -25 Rr: -35 to -15	Ft: -55 to -21 Rr: -47 to -14		When installing on Move Custom (Dec 08 - Dec 10) fog light position is less than 250mm from the ground and will not comply with vehicle safety regulations. Rr: Due to individual differences, interior needs to be cut or removed if interferes.
DAIHATSU	MOVE / MOVE CUSTOM LA100S 660cc / FWD	GSD52-21AS2 JPY99,000 JAN: 4582202756429	Ft: I.D.70 5.0k 200mm Rr: Exclusive Spring 2.4k	Ft: -45mm Rr: -40mm	Ft: -55 to -35 Rr: -50 to -30	Ft: -65 to -15 Rr: -62 to -30	NOT Compatible	
DAIHATSU	MOVE CONTE L575S 660cc / FWD	GSD36-21AS2 JPY99,000 JAN: 4582202756405	Ft: I.D.70 3.0k 225mm Rr: Exclusive Spring 2.4k	Ft: -45mm Rr: -35mm	Ft: -55 to -35 Rr: -45 to -25	Ft: -65 to -31 Rr: -57 to -24		When installing on Move Conte Custom fog light position is less than 250mm from the ground and will not comply with vehicle safety regulations. Rr: Due to individual differences, interior needs to be cut or removed if interferes.



For product information, please contact: TEIN INC. Sales Section Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123 http://www.tein.co.jp/global\_en.html E-mail os-inquiry@tein.co.jp

