

NEW PRODUCT GUIDE



STREET ADVANCE & STREET BASIS for GOLF V & VI Available Soon!

STREET ADVANCE DAMPER

Vehicle Make / Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
VW GOLF 5 (GT) 1KBLX 2000cc / FWD	GSJ78-21AS2 JPY 110,000 JAN: 4582202756504	Ft: I.D.70-90 6.0k 200mm Rr: Exclusive Spring 5.0k	Ft: -30mm Rr: -25mm	Ft: -40 to -20 Rr: -35 to -15	Ft: -45 to -10 Rr: -52 to -6	Early June	NOT Compatible	Ft: Exclusively for vehicle with 55mm diameter OE strut. Rr: Use with OE bump rubber & dust boot. Spring insulator needs to be modified. Spring Seat position: Ft=-5mm compared to 1KAXX (GTI) NOT tested on vehicle equipped with optional racing stabilizer.
VW GOLF 5 (GTI) 1KAXX 2000cc / FWD			Ft: -30mm Rr: -25mm	Ft: -40 to -20 Rr: -35 to -15	Ft: -50 to -15 Rr: -52 to -6			Ft: Exclusively for vehicle with 55mm diameter OE strut. Rr: Use with OE bump rubber & dust boot. Spring insulator needs to be modified. NOT tested on vehicle equipped with optional racing stabilizer. NOT compatible with early model with auto headlight height adjustment feature, due to the difference in sensor bracket shape. Refer to Pg.14 of the manual for details.
VW GOLF 5 (GT TSI) 1KBLG 1400cc / FWD			Ft: -30mm Rr: -35mm	Ft: -40 to -20 Rr: -45 to -25	Ft: -50 to -15 Rr: -62 to -16			Ft: Exclusively for vehicle with 55mm diameter OE strut. Rr: Use with OE bump rubber & dust boot. Spring insulator needs to be modified. NOT tested on vehicle equipped with optional racing stabilizer.
VW GOLF 6 (TSI HIGHLINE) 1KCAV 1400cc / FWD			Ft: -30mm Rr: -45mm	Ft: -40 to -20 Rr: -55 to -35	Ft: -50 to -15 Rr: -72 to -26			Exclusively for vehicle NOT equipped with DCC. Ft: Exclusively for vehicle with 55mm diameter OE strut. Rr: Use with OE bump rubber & dust boot. Spring insulator needs to be modified.
VW GOLF 6 (GTI) 1KCCZ 2000cc / FWD			Ft: -25mm Rr: -30mm	Ft: -35 to -15 Rr: -40 to -20	Ft: -50 to -16 Rr: -57 to -11			Exclusively for vehicle NOT equipped with DCC. Ft: Exclusively for vehicle with 55mm diameter OE strut. Rr: Use with OE bump rubber & dust boot. Spring insulator needs to be modified. Spring Seat position: Ft=+5mm compared to 1KCAV (TSI HIGHLINE)

Shapes of sensor bracket, for GOLF 5 with auto headlight adjustment system



compatible



NOT compatible

NEW PRODUCT GUIDE



STREET BASIS DAMPER

Vehicle Make / Model Chassis Code	Kit w/o Upper Mount Part No. / MSRP	Set Spring	Ride Height Drop	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	Remarks
VW GOLF 5 (GT) 1KBLX 2000cc / FWD	GSJ78-11AS2 JPY 95,000 JAN: 4582202757211	Ft: I.D.70-90 6.0k 200mm Rr: Exclusive Spring 5.0k	Ft: -30mm Rr: -25mm	Ft: -40 to -20 Rr: -35 to -15	Ft: -45 to -10 Rr: -52 to -6	Early June	Ft: Exclusively for vehicle with 55mm diameter OE strut. Rr: Use with OE bump rubber & dust boot. Spring insulator needs to be modified. Spring Seat position: Ft=-5mm compared to 1KAXX (GTI) NOT tested on vehicle equipped with optional racing stabilizer.
VW GOLF 5 (GTI) 1KAXX 2000cc / FWD			Ft: -30mm Rr: -25mm	Ft: -40 to -20 Rr: -35 to -15	Ft: -50 to -15 Rr: -52 to -6		Ft: Exclusively for vehicle with 55mm diameter OE strut. Rr: Use with OE bump rubber & dust boot. Spring insulator needs to be modified. NOT tested on vehicle equipped with optional racing stabilizer. NOT compatible with early model with auto headlight height adjustment feature, due to the difference in sensor bracket shape. Refer to Pg.14 of the manual for details.
VW GOLF 5 (GT TSI) 1KBLG 1400cc / FWD			Ft: -30mm Rr: -35mm	Ft: -40 to -20 Rr: -45 to -25	Ft: -50 to -15 Rr: -62 to -16		Ft: Exclusively for vehicle with 55mm diameter OE strut. Rr: Use with OE bump rubber & dust boot. Spring insulator needs to be modified. NOT tested on vehicle equipped with optional racing stabilizer.
VW GOLF 6 (TSI HIGHLINE) 1KCAV 1400cc / FWD			Ft: -30mm Rr: -45mm	Ft: -40 to -20 Rr: -55 to -35	Ft: -50 to -15 Rr: -72 to -26		Exclusively for vehicle NOT equipped with DCC. Ft: Exclusively for vehicle with 55mm diameter OE strut. Rr: Use with OE bump rubber & dust boot. Spring insulator needs to be modified.
VW GOLF 6 (GTI) 1KCCZ 2000cc / FWD			Ft: -25mm Rr: -30mm	Ft: -35 to -15 Rr: -40 to -20	Ft: -50 to -16 Rr: -57 to -11		Exclusively for vehicle NOT equipped with DCC. Ft: Exclusively for vehicle with 55mm diameter OE strut. Rr: Use with OE bump rubber & dust boot. Spring insulator needs to be modified. Spring Seat position: Ft=+5mm compared to 1KCAV (TSI HIGHLINE)

*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection. TEIN dampers are designed to comply with the regulations at the standard ride height drop.

For product information, please contact:
 TEIN INC. Sales Section
 Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123
http://www.tein.co.jp/global_en.html
 E-mail os-inquiry@tein.co.jp

