

## NEW PRODUCT GUIDE



# STREET FLEX Coming Soon!

## for HONDA NSX (NA1) & MITSUBISHI Lancer Evolution (CN/CP9A)

# STREET FLEX

DAMPER

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
HONDA NSX NA1 3000 cc / RWD	GSH14-51SS3 JPY 128,000 JAN : 4582202758331	Ft : 10.0 Rr : 12.0	Ft : -50 Rr : -30	Ft : -60 to -40 Rr : -40 to -20	Ft : -101 to +17 Rr : -97 to +2	Late June	EDK05-12120	[Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed, if interferes. Rr: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle.
MITSUBISHI LANCER EVOLUTION IV CN9A 2000 cc / AWD	GSR10-51SS4 JPY 148,000 JAN : 4582202758317	Ft : 8.0 Rr : 7.0	Ft : -45 Rr : -20	Ft : -55 to -35 Rr : -30 to -10	Ft : -127 to -14 Rr : -80 to +56	Late June	EDK05-12140 [STRUT KIT] EDK06-K4474	[Upon EDFC Installation] Rr: Interior cover needs to be removed, if it interferes with motor.
MITSUBISHI LANCER EVOLUTION V CP9A 2000 cc / AWD	GSR10-51SS4 JPY 148,000 JAN : 4582202758317	Ft : 8.0 Rr : 7.0	Ft : -45 Rr : -15	Ft : -55 to -35 Rr : -25 to -5	Ft : -127 to -14 Rr : -75 to +61	Late June	EDK05-12140 [STRUT KIT] EDK06-K4474	[Upon EDFC Installation] Rr: Interior cover needs to be removed, if it interferes with motor.
MITSUBISHI LANCER EVOLUTION VI CP9A 2000 cc / AWD	GSR10-51SS4 JPY 148,000 JAN : 4582202758317	Ft : 8.0 Rr : 7.0	Ft : -50 Rr : -15	Ft : -60 to -40 Rr : -25 to -5	Ft : -132 to -19 Rr : -75 to +61	Late June	EDK05-12140 [STRUT KIT] EDK06-K4474	[Upon EDFC Installation] Rr: Interior cover needs to be removed, if it interferes with motor.
MITSUBISHI LANCER EVOLUTION VI CP9A 2000 cc / AWD	GSR10-51SS4 JPY 148,000 JAN : 4582202758317	Ft : 8.0 Rr : 7.0	Ft : -45 Rr : -15	Ft : -55 to -35 Rr : -25 to -5	Ft : -127 to -14 Rr : -75 to +61	Late June	EDK05-12140 [STRUT KIT] EDK06-K4474	[Upon EDFC Installation] Rr: Interior cover needs to be removed, if it interferes with motor.

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

\*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp).

Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations.

For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection.

TEINI dampers are designed to comply with the regulations at the standard ride height drop.

# COMPATIBILITY INFORMATION



## Compatibility Confirmed on TOYOTA Alphard / Vellfire G's, NISSAN Serena S-Hybrid & HONDA N BOX AWD !



Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	Remarks
TOYOTA ALPHARD / VELLFIRE ANH20W (240S G's / 2.4Z G's) 2400 cc / FWD	GSC78-11AS2 JPY 90,000 JAN : 4582202755033	Ft : 4.0 Rr : 6.0	Ft : -20 Rr : -15	Ft : -30 to -10 Rr : -25 to -5	Ft : -45 to +10 Rr : -40 to -5	Available Now!	Spring seat position: Ft = 30mm / Rr = HAS 48mm
TOYOTA ALPHARD / VELLFIRE GGH20W (350S G's / 3.5Z G's) 3500 cc / FWD	GSC86-11AS2 JPY 90,000 JAN : 4582202755040	Ft : 5.0 Rr : 6.0	Ft : -15 Rr : -10	Ft : -25 to -5 Rr : -20 to 0	Ft : -45 to +10 Rr : -20 to +15	Available Now!	Spring seat position: Ft = 30mm / Rr = HAS 34mm
NISSAN SERENA HC26 2000 cc / FWD	GSK28-11AS2 JPY 90,000 JAN : 4582202755620	Ft : 5.0 Rr : 7.0	Ft : -45 Rr : -45	Ft : -55 to -35 Rr : -55 to -36	Ft : -75 to -35 Rr : -73 to -36	Available Now!	Spring seat position: Ft = 35mm / Rr = HAS 48mm
HONDA N BOX JF2 660 cc / AWD	GSHC4-11AS2 JPY 84,000 JAN : 4582202758461	Ft : 3.0 Rr : 4.0	Ft : -40 Rr : -55	Ft : -50 to -30 Rr : -65 to -45	Ft : -55 to -27 Rr : -80 to -45	Available Now!	Spring seat position: Ft = 20mm / Rr = HAS 50mm



Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
TOYOTA ALPHARD / VELLFIRE ANH20W (240S G's / 2.4Z G's) 2400 cc / FWD	GSC78-21AS2 JPY 105,000 JAN : 4582202756238	Ft : 4.0 Rr : 6.0	Ft : -20 Rr : -15	Ft : -30 to -10 Rr : -25 to -5	Ft : -45 to +10 Rr : -40 to -5	Available Now!	EDK05-12140	Spring seat position: Ft = 30mm / Rr = HAS 48mm [Upon EDFC Installation] Rr: Service hole cover needs to be cut or removed. Motor needs to be installed parallel to the vehicle body. Need to take precaution when sliding 3rd-row seat, due to insufficient clearance with motor.
TOYOTA ALPHARD / VELLFIRE GGH20W (350S G's / 3.5Z G's) 3500 cc / FWD	GSC86-21AS2 JPY 105,000 JAN : 4582202756382	Ft : 5.0 Rr : 6.0	Ft : -15 Rr : -10	Ft : -25 to -5 Rr : -20 to 0	Ft : -45 to +10 Rr : -20 to +15	Available Now!	EDK05-12140	Spring seat position: Ft = 30mm / Rr = HAS 34mm [Upon EDFC Installation] Rr: Service hole cover needs to be cut or removed. Motor needs to be installed parallel to the vehicle body. Need to take precaution when sliding 3rd-row seat, due to insufficient clearance with motor.
NISSAN SERENA HC26 2000 cc / FWD	GSK28-21AS2 JPY 105,000 JAN : 4582202756542	Ft : 5.0 Rr : 7.0	Ft : -45 Rr : -45	Ft : -55 to -35 Rr : -55 to -36	Ft : -75 to -35 Rr : -73 to -36	Available Now!	NOT Compatible	Spring seat position: Ft = 35mm / Rr = HAS 48mm

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

\*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection. TEINI dampers are designed to comply with the regulations at the standard ride height drop.

## COMPATIBILITY INFORMATION



# Compatibility Confirmed on TOYOTA Alphard / Vellfire G's & NISSAN Serena S-Hybrid !

## STREET FLEX DAMPER

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
TOYOTA ALPHARD / VELLFIRE ANH20W (240S G's / 2.4Z G's) 2400 cc / FWD	GSC78-51AS3 JPY 148,000 JAN : 4582202757365	Ft : 5.0 Rr : 7.0	Ft : -20 Rr : -15	Ft : -30 to -10 Rr : -25 to -5	Ft : -60 to +14 Rr : -35 to -1	Available Now!	EDK05-12120	Spring seat position: Ft = 160mm / Rr = HAS 44mm [Upon EDFC Installation] Rr: Service hole cover needs to be cut or removed. Motor needs to be installed parallel to the vehicle body. Need to take precaution when sliding 3rd-row seat, due to insufficient clearance with motor.
TOYOTA ALPHARD / VELLFIRE GGH20W (350S G's / 3.5Z G's) 3500 cc / FWD	GSC78-51AS3 JPY 148,000 JAN : 4582202757365	Ft : 5.0 Rr : 7.0	Ft : -20 Rr : -15	Ft : -30 to -10 Rr : -25 to -5	Ft : -75 to +14 Rr : -35 to -1	Available Now!	EDK05-12120	Spring seat position: Ft = 175mm / Rr = HAS 44mm. For vehicle (weight approx. 2,000kg & over) equipped with optional parts (e.g. twin moonroof), use of "GSC86-51AS3" recommended. [Upon EDFC Installation] Rr: Service hole cover needs to be cut or removed. Motor needs to be installed parallel to the vehicle body. Need to take precaution when sliding 3rd-row seat, due to insufficient clearance with motor.
NISSAN SERENA HC26 2000 cc / FWD	GSK28-51AS3 JPY 148,000 JAN : 4582202757525	Ft : 5.0 Rr : 7.0	Ft : -45 Rr : -45	Ft : -55 to -35 Rr : -55 to -36	Ft : -95 to -30 Rr : -73 to -36	Available Now!	NOT Compatible	Spring seat position: Ft = 166mm / Rr = HAS 48mm

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

\*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp).

Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations.

For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection.

TEIN dampers are designed to comply with the regulations at the standard ride height drop.

### For product information, please contact:

TEIN INC. Sales Section  
Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123  
[http://www.tein.co.jp/global\\_en.html](http://www.tein.co.jp/global_en.html)  
E-mail [os-inquiry@tein.co.jp](mailto:os-inquiry@tein.co.jp)

