

**NEW PRODUCT GUIDE**



## Popular "STREET FLEX" kit for NISSAN 180SX / Silvia (S13) Available Soon!



Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks						
NISSAN 180SX RS13 1800 cc / RWD	GSN20-51SS4 JPY 148,000 JAN : 4582202758195	Ft : 7.0 Rr : 5.0	Ft : -45 Rr : -25	Ft : -55 to -35 Rr : -35 to -15	Ft : -109 to -25 Rr : -105 to +9	Late May	EDK05-12140 [STRUT KIT] EDK06-K4474	[Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed. Rr: Body panel might need to be modified (bent), if clearance between motor and body panel is insufficient. Interior needs to be cut or removed.						
NISSAN 180SX KRS13 1800 cc / RWD														
NISSAN 180SX RPS13 2000 cc / RWD														
NISSAN 180SX KRPS13 2000 cc / RWD														
NISSAN SILVIA S13 1800 cc / RWD														
NISSAN SILVIA PS13 2000 cc / RWD														[Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed, to avoid interference. Rr: Interior needs to be cut or removed, if it interferes with motor.
NISSAN SILVIA KPS13 2000 cc / RWD														

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

\*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp). Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations. For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection. TEIN dampers are designed to comply with the regulations at the standard ride height drop.

## NEW PRODUCT GUIDE

### More & More "STREET FLEX" Applications! for HONDA Legend / Integra / Integra Type R & MITSUBISHI Colt Ralliart Version-R!

## STREET FLEX

DAMPER

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
HONDA LEGEND KB1 3500 cc / AWD	GSB22-51AS3 JPY 138,000 JAN : 4582202758041	Ft : 12.0 Rr : 10.0	Ft : -30 Rr : -20	Ft : -40 to -20 Rr : -30 to -10	Ft : -115 to 0 Rr : -52 to -4	Late May	EDK05-12120	[Upon EDFC Installation] Ft: Fender garnish (cover on engine bay) needs to be cut or removed.
HONDA LEGEND KB2 3700 cc / AWD			Ft : -30 Rr : -30	Ft : -40 to -20 Rr : -40 to -20	Ft : -115 to 0 Rr : -62 to -14			
HONDA INTEGRA DC5 ( 2001.07-2004.09 ) 2000 cc / FWD	GSA02-51SS1 JPY 178,000 JAN : 4582202757884	Ft : 8.0 Rr : 10.0	Ft : -30 Rr : -30	Ft : -40 to -20 Rr : -40 to -20	Ft : -56 to -2 Rr : -64 to -5	Late May	EDK05-12140 [STRUT KIT] EDK06-K4474	Because the adjustable range of the camber angle is limited due to the vehicle characteristics, adjust the angle within the appropriate adjustable range of the toe angle.
HONDA INTEGRA TYPE R DC5 ( 2001.07-2004.09 ) 2000 cc / FWD								[Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed.
HONDA INTEGRA DC5 ( 2004.09-2006.07 ) 2000 cc / FWD								Because the adjustable range of the camber angle is limited due to the vehicle characteristics, adjust the angle within the appropriate adjustable range of the toe angle.
HONDA INTEGRA TYPE R DC5 ( 2004.09-2006.07 ) 2000 cc / FWD								[Upon EDFC Installation] Ft: Bonnet/hood insulator needs to be cut or removed. OE strut bar needs to be removed.
MITSUBISHI COLT RALLIART VERSION-R Z27AG 1500 cc / FWD	GSE10-51AS1 JPY 148,000 JAN : 4582202758263	Ft : 5.0 Rr : 4.0	Ft : -30 Rr : -25	Ft : -40 to -20 Rr : -35 to -15	Ft : -78 to -6 Rr : -53 to -7	Late May	EDK05-10140 [STRUT KIT] EDK06-K4474	Ft: Use of EDFC is recommended, as it is difficult to adjust damping force manually due to vehicle structure.  [Upon EDFC Installation] Ft: Motor needs to be installed onto shock absorber and checked for proper operation, before installing to the vehicle. Rr: Service hole cover needs to be cut or removed.

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

\*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp).

Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations.

For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection.

TEIN dampers are designed to comply with the regulations at the standard ride height drop.

## COMPATIBILITY INFORMATION



### Compatibility Confirmed on TOYOTA Crown Hybrid Royal Saloon (AWS210) !

## STREET FLEX DAMPER

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
TOYOTA CROWN HYBRID AWS210 ( ROYAL SALOON ) 2500 cc / RWD	GSC76-51SS3 JPY 128,000 JAN : 4582202757433	Ft : 10.0 Rr : 8.0	Ft : -45 Rr : -45	Ft : -55 to -35 Rr : -55 to -35	Ft : -113 to +31 Rr : -144 to -7	Available Now!	EDK05-12120	Due to individual differences, inner fender may need to be cut if it interferes with the spring. Case Length: Ft/Rr=-4/+7MM compared to GRS200.

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

## LOWDOWN SPEC COMFORT CRUISING MASTER FLEX

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
TOYOTA CROWN HYBRID AWS210 ( ROYAL SALOON ) 2500 cc / RWD	GSC76-F1SS3 JPY 191,000 JAN : 4582202753916	Ft : 10.0 Rr : 8.0	Ft : -45 Rr : -45	Ft : -55 to -35 Rr : -55 to -35	Ft : -109 to +13 Rr : -135 to -25	Available Now!	EDK05-12120	Due to individual differences, inner fender may need to be cut if it interferes with the spring. Ft: Set case length +1mm, and the position of spring seat -2mm compared to GRS200. Rr: Set case length +7mm compared to GRS200.

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

## PREMIUM SPEC COMFORT CRUISING MASTER SPORT

Vehicle Make / Model Chassis Code Displacement / Drive-Train	Kit Part No. MSRP	Set Spring (kgf/mm)	Ride Height Drop(mm)	Recommended Ride Height Adjustment Range (mm)	Ride Height Adjustable Range (mm)	Release Date	EDFC Fitting	Remarks
TOYOTA CROWN HYBRID AWS210 ( ROYAL SALOON ) 2500 cc / RWD	GSC76-K1SS3 JPY 167,000 JAN : 4582202753435	Ft : 7.0 Rr : 7.0	Ft : -45 Rr : -45	Ft : -55 to -35 Rr : -55 to -35	Ft : -60 to -23 Rr : -78 to -22	Available Now!	EDK05-12120	Spring seat position: Ft/Rr=-7/+3mm, compared to GRS200.

\*For EDFC, Controller kit (sold separately) is required, in addition to Motor / Strut Kit noted in the chart.

\*For vehicles manufactured on or after January 1st, 2006, there's a new regulation in place, limiting the position of light/lamp (e.g. fog light, turn-signal lamp).

Please adjust the ride height to secure the minimum ground clearance from such light/lamp, to comply with Japan's vehicle safety regulations.

For details on inspection standards, please contact the nearest National Agency of Vehicle Inspection.

TEIN dampers are designed to comply with the regulations at the standard ride height drop.

**For product information, please contact:**

TEIN INC. Sales Section

Phone (+81) 45-810-5501 / Fax (+81) 50-3156-3123

[http://www.tein.co.jp/global\\_en.html](http://www.tein.co.jp/global_en.html)

E-mail [os-inquiry@tein.co.jp](mailto:os-inquiry@tein.co.jp)

